## Air Conditioning

## **Product Information**

**GUF-100RD4: Lossnay Outdoor Air** 

**Processing Unit** 

R410A





The GUF-RD4 Outdoor Air Processing Units can be used with any of the extensive range of City Multi indoor units to provide ventilation, dust removal, humidification and heat recovery.



## **FEATURES**













INDOOR	
Heating Capacity (kW) (nominal)	12.56 (4.26)
Cooling Capacity (kW) (nominal)	11.44 (4.12)
High Performance Heating Capacity (kW) (UK)	13.00 (4.70)
COP Priority Heating Capacity (kW) (UK)	12.01 (4.34)
Cooling Capacity (kW) (UK)	10.27 (3.32)
Heating Power Input (kW) - Hi	0.505
Cooling Power Input (kW) - Hi	0.505
Airflow (m³/min) - Lo-Hi	13.33 - 16.67
External Static Pressure (Pa)	140
Sound Pressure Level (dBA) - Lo-Hi	34 - 39
Weight (kg)	92
Dimensions (mm) Width	1231
Dimensions (mm) Depth	1580
Dimensions (mm) Height	398
Electrical Supply	220-240V, 50HZ
Phase	SINGLE
Running Current (A) - Heating / Cooling - Hi	2.2 / 2.2
Fuse Rating (BS88) - HRC (A)	6
Mains Cable No. Cores	3

## **DIMENSIONS**

GUF-100RD4







