

## PFD-P500VM-E

Downflow Indoor Unit

R410A Heat Pump Close Control System

Mitsubishi Electric's new Close Control System is specifically designed for computer rooms, laboratories etc, where a need for high sensible cooling and close control of temperature and humidity is required. Because of the need for close control 24 hours a day, 365 days a year, a newly developed inverter driven compressor has been incorporated into the outdoor unit, maximising the energy efficiency of the PFD series. It is also able to be connected to a computer network using our G50 Controller, in order to monitor and provide remote email alarms.

- High Sensible Cooling
- Energy efficient with high COP's
- Close control of temperature, ±1°C
- Easy to install no service space needed at the rear of the unit
- Optional third party humidifier available
- Quick recovery following power failure
- Improved pipe runs connects to PUHY-P500YGM-A outdoor unit
- Return or discharge air temperature control




Pictures not to scale




PFD-P500VM-E	
Capacity (kW):	
Heating (Nominal)	63.0
Cooling (Nominal)	56.0
Heating (UK)	55.4
Cooling (UK)	51.5
SHF R410A (UK)	0.93
Power Input (kW) Heating (Nominal)	5
Power Input (kW) Cooling (Nominal)	5
Power Input (kW) Heating (UK)	4.3
Power Input (kW) Cooling (UK)	4.3
Airflow(m3/min)	320
External Static Pressure Pa	120
Noise (dBA)	63
Pipe Size Gas mm (in)	28.58 (1 1/8)
Pipe Size Liquid mm (in)	15.88 (5/8)
Width - mm	1980
Depth - mm	780
Height - mm	1950
Weight - kg	520
Electrical Supply	380-415v, 50Hz
Phase	3
Mains Cable No. Cores	4 + earth
Starting Current (A)	68
Running Current (A) - Heating	8.7
Running Current (A) - Cooling	8.7
Fuse Rating (BS88) - HRC (A)	20
Piping Restrictions	
Total Piping Length (m)	150
	130

_		ısi		

PFD-P500VM-E



주 Air outlet 주 Control box





Between Indoor and Outdoor Units - Height

## Telephone: 01707 282880

50

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.



(m)

