



# PFFY-P32VLEM-E

Indoor Unit

Floor Standing Exposed

A compact cased unit providing simple, effective air conditioning in perimeter zones. The unit is easy to install and at only 220mm deep offers an unobtrusive method of delivering a highly efficient air-conditioning performance.

- **Remote controller can be incorporated into the main unit**
- **Cooling operation set temperature can be set down to 14°C db when used with R410A**






Pictures not to scale



PFFY-P32VLEM-E	
Capacity (kW):	
Heating (Nominal)	4.0
Cooling (Nominal)	3.6
Heating (UK)	3.7
Cooling (UK)	3.4
R410A High Sensible Cooling (UK)	2.6
SHF R410A (UK)	0.74
SHF High Sensible R410A (UK)	0.81
Power Input (kW) Heating (Nominal)	0.06
Power Input (kW) Cooling (Nominal)	0.06
Airflow(m3/min) - Lo-Hi	7-9
Noise (dBA) - Lo-Hi	35-40
Width - mm	1170
Depth - mm	220
Height - mm	630
Weight - kg	25
Electrical Supply	220-240v, 50Hz
Phase	Single
Mains Cable No. Cores	3
Running Current (A) - Heating	0.29
Running Current (A) - Cooling	0.29
Fuse Rating (BS88) - HRC (A)	6

## PFFY-P32VLEM-E



Email: [air.conditioning@meuk.mee.com](mailto:air.conditioning@meuk.mee.com) Website: <http://www.mitsubishielectric.co.uk/aircon>

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.



**Tel:**  
**Fax:**