Air Conditioning

Product Information

PFFY-P40VLRM-E: Indoor Unit

Floor Standing Concealed





A compact concealed unit providing simple, effective air conditioning in perimeter zones. The unit is easy to install and at only 220mm deep offers an unobtrusive method of delivering highly efficient air-conditioning performance.



FEATURES













Heating Capacity (kW) (nominal)		
Cooling Capacity (kW) (nominal) 4.5 High Performance Heating Capacity (kW) (UK) 5 COP Priority Heating Capacity (kW) (UK) 4.5 Cooling Capacity (kW) (UK) 4.5 Cooling Capacity (Hi-Sens Mode) (kW) (UK) 3.5 SHF (UK) 0.77 SHF (Hi-Sens Mode) (UK) 0.75 Heating Power Input (kW) (nominal) 0.068 Cooling Power Input (kW) (nominal) 0.068 Airflow (m³/min) - Lo-Hi 9 - 1 Sound Pressure Level (dBA) - Lo-Hi 38 - 43 Weight (kg) 2° Dimensions (mm) Width 1000 Dimensions (mm) Depth 220 Dimensions (mm) Height 639 Electrical Supply 220-240V, 50Hz Phase SINGLE Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A) 6	INDOOR	
High Performance Heating Capacity (kW) (UK)	Heating Capacity (kW) (nominal)	5
COP Priority Heating Capacity (kW) (UK) 4.3. Cooling Capacity (kW) (UK) 4.3. Cooling Capacity (Hi-Sens Mode) (kW) (UK) 3.3. SHF (UK) 0.72 SHF (Hi-Sens Mode) (UK) 0.75 Heating Power Input (kW) (nominal) 0.068 Cooling Power Input (kW) (nominal) 0.068 Airflow (m³/min) - Lo-Hi 9 - 11 Sound Pressure Level (dBA) - Lo-Hi 38 - 43 Weight (kg) 22 Dimensions (mm) Width 1006 Dimensions (mm) Depth 220 Dimensions (mm) Depth 220 Dimensions (mm) Height 638 Electrical Supply 220-240V, 50Hz Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A)	Cooling Capacity (kW) (nominal)	4.5
Cooling Capacity (kW) (UK) 4.3 Cooling Capacity (Hi-Sens Mode) (kW) (UK) 3.3 SHF (UK) 0.75 SHF (Hi-Sens Mode) (UK) 0.75 Heating Power Input (kW) (nominal) 0.06 Cooling Power Input (kW) (nominal) 0.06 Airflow (m³/min) - Lo-Hi 9 - 1 Sound Pressure Level (dBA) - Lo-Hi 38 - 43 Weight (kg) 2° Dimensions (mm) Width 100 Dimensions (mm) Depth 220 Dimensions (mm) Height 635 Electrical Supply 220-240V, 50Hz Phase SINGLE Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A) 6	High Performance Heating Capacity (kW) (UK)	5
Cooling Capacity (Hi-Sens Mode) (kW) (UK) 3.3 SHF (UK) 0.72 SHF (Hi-Sens Mode) (UK) 0.75 Heating Power Input (kW) (nominal) 0.06 Cooling Power Input (kW) (nominal) 0.06 Airflow (m³/min) - Lo-Hi 9 - 1* Sound Pressure Level (dBA) - Lo-Hi 38 - 43 Weight (kg) 2* Dimensions (mm) Width 1000 Dimensions (mm) Depth 220 Dimensions (mm) Height 636 Electrical Supply 220-240V, 50Hz Phase SINGLE Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A) 6	COP Priority Heating Capacity (kW) (UK)	4.7
SHF (UK) 0.75 SHF (Hi-Sens Mode) (UK) 0.75 Heating Power Input (kW) (nominal) 0.068 Cooling Power Input (kW) (nominal) 0.066 Airflow (m³/min) - Lo-Hi 9 - 1* Sound Pressure Level (dBA) - Lo-Hi 38 - 45 Weight (kg) 2* Dimensions (mm) Width 1000 Dimensions (mm) Depth 220 Dimensions (mm) Height 636 Electrical Supply 220-240V, 50Hz Phase SINGLE Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A) 6	Cooling Capacity (kW) (UK)	4.3
SHF (Hi-Sens Mode) (UK) 0.75 Heating Power Input (kW) (nominal) 0.068 Cooling Power Input (kW) (nominal) 0.068 Airflow (m³/min) - Lo-Hi 9 - 1* Sound Pressure Level (dBA) - Lo-Hi 38 - 4 Weight (kg) 2* Dimensions (mm) Width 1006 Dimensions (mm) Depth 220 Dimensions (mm) Height 63 Electrical Supply 220-240V, 50Hz Phase SINGLE Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A) 68	Cooling Capacity (Hi-Sens Mode) (kW) (UK)	3.3
Heating Power Input (kW) (nominal) 0.068 Cooling Power Input (kW) (nominal) 0.068 Airflow (m³/min) - Lo-Hi 9 - 1* Sound Pressure Level (dBA) - Lo-Hi 38 - 4* Weight (kg) 2* Dimensions (mm) Width 1006 Dimensions (mm) Depth 220 Dimensions (mm) Height 638 Electrical Supply 220-240V, 50Hz Phase SINGLE Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A) 6	SHF (UK)	0.72
Cooling Power Input (kW) (nominal) 0.068 Airflow (m³/min) - Lo-Hi 9 - 1 Sound Pressure Level (dBA) - Lo-Hi 38 - 4 Weight (kg) 2° Dimensions (mm) Width 1006 Dimensions (mm) Depth 220 Dimensions (mm) Height 638 Electrical Supply 220-240V, 50Hz Phase SINGLE Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A) 6	SHF (Hi-Sens Mode) (UK)	0.79
Airflow (m³/min) - Lo-Hi 9 - 1 Sound Pressure Level (dBA) - Lo-Hi 38 - 4 Weight (kg) 2 Dimensions (mm) Width 1006 Dimensions (mm) Depth 220 Dimensions (mm) Height 638 Electrical Supply 220-240V, 50Hz Phase SINGLE Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A) 6	Heating Power Input (kW) (nominal)	0.065
Sound Pressure Level (dBA) - Lo-Hi 38 - 43 Weight (kg) 2° Dimensions (mm) Width 1006 Dimensions (mm) Depth 220 Dimensions (mm) Height 638 Electrical Supply 220-240V, 50Hz Phase SINGLE Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A) 6	Cooling Power Input (kW) (nominal)	0.065
Weight (kg) 2** Dimensions (mm) Width 1006 Dimensions (mm) Depth 220 Dimensions (mm) Height 638 Electrical Supply 220-240V, 50Hz Phase SINGLE Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A) 6	Airflow (m³/min) - Lo-Hi	9 - 11
Dimensions (mm) Width 1006 Dimensions (mm) Depth 220 Dimensions (mm) Height 638 Electrical Supply 220-240V, 50Hz Phase SINGLE Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A) 6	Sound Pressure Level (dBA) - Lo-Hi	38 - 43
Dimensions (mm) Depth 220 Dimensions (mm) Height 638 Electrical Supply 220-240V, 50Hz Phase SINGLE Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A) 6	Weight (kg)	21
Dimensions (mm) Height 638 Electrical Supply 220-240V, 50Hz Phase SINGLE Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A) 68	Dimensions (mm) Width	1006
Electrical Supply 220-240V, 50Hz Phase SINGLE Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A) 6	Dimensions (mm) Depth	220
Phase SINGLE Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A) 6	Dimensions (mm) Height	639
Running Current (A) - Heating / Cooling 0.32 / 0.32 Fuse Rating (BS88) - HRC (A)	Electrical Supply	220-240V, 50HZ
Fuse Rating (BS88) - HRC (A)	Phase	SINGLE
	Running Current (A) - Heating / Cooling	0.32 / 0.32
Mains Cable No. Cores	Fuse Rating (BS88) - HRC (A)	6
	Mains Cable No. Cores	3





