Air Conditioning

Product Information

PFFY-P63VLRMM-E: Indoor Unit

Floor Standing Concealed





A compact concealed unit providing simple, effective air conditioning in perimeter zones. The unit is easy to install and at only 220mm deep offers an unobtrusive method of delivering highly efficient air-conditioning performance.



FEATURES













INDOOR	
Heating Capacity (kW) (nominal)	8
Cooling Capacity (kW) (nominal)	7.1
High Performance Heating Capacity (kW) (UK)	8
COP Priority Heating Capacity (kW) (UK)	7.5
Cooling Capacity (kW) (UK)	6.7
Cooling Capacity (Hi-Sens Mode) (kW) (UK)	5.2
SHF (UK)	0.73
SHF (Hi-Sens Mode) (UK)	0.79
Heating Power Input (kW) (nominal)	0.07
Cooling Power Input (kW) (nominal)	0.07
Airflow (m³/min) - Lo-Mi-Hi	11 - 13 - 15.5
External Static Pressure (Pa)	20 - 40 - 60
Sound Pressure Level (dBA) - Lo-Mi-Hi	35 - 40 - 44
Weight (kg)	27
Dimensions (mm) Width	1246
Dimensions (mm) Depth	220
Dimensions (mm) Height	639
Electrical Supply	220-240V, 50HZ
Phase	SINGLE
Running Current (A) - Heating / Cooling	0.59 / 0.59
Fuse Rating (BS88) - HRC (A)	6
Mains Cable No. Cores	3

DIMENSIONS

PFFY-P63VLRMM-E





