Air Conditioning

Product Information PKFY-P25VBM-E : Indoor Unit Wall Mounted





An elegant design combined with compact dimensions and quiet operation make the PKFY-P an ideal unit choice. Noise levels are significantly reduced thanks to a unique airflow passage design that not only makes the unit one of the quietest in the industry, but also suppresses condensation and prevents mixing with secondary air.



FEATURES







Q








INDOOR

DIMENSIONS


Heating Capacity (kW) (nominal) 3.2 2.8 Cooling Capacity (kW) (nominal) 3.2 High Performance Heating Capacity (kW) (UK) COP Priority Heating Capacity (kW) (UK) 3 Cooling Capacity (kW) (UK) 2.7 Cooling Capacity (Hi-Sens Mode) (kW) (UK) 2 SHF (UK) 0.7 SHF (Hi-Sens Mode) (UK) 0.8 Heating Power Input (kW) (nominal) 0.04 Cooling Power Input (kW) (nominal) 0.04 Airflow (m³/min) - Lo-Mi1-Mi2-Hi 4.9 - 5.2 - 5.6 - 5.9 Sound Pressure Level (dBA) - Lo-Mi1-Mi2-Hi 29 - 31 - 34 - 36 Weight (kg) 10 Dimensions (mm) Width 815 Dimensions (mm) Depth 225 Dimensions (mm) Height 295 Electrical Supply 220-240V, 50HZ Phase SINGLE Running Current (A) - Heating / Cooling 0.2 / 0.2 Fuse Rating (BS88) - HRC (A) 6 Mains Cable No. Cores 3

PKFY-P25VBM-E





Right Side View >



PKFY-P20, 25VBM-E



CE

Telephone: 01707 282880 Fax: 01707 278881 Email: airconditioning@meuk.mee.com Website: http://www.airconditioning.mitsubishielectric.co.uk

Country of origin: United Kingdom – Japan – Thailand – Malaysia.

Mitsubishi Electric Europe 2013. Mitsubishi and Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks of their respective owners.