Air Conditioning

Product Information

PLFY-P63VLMD-E: Indoor Unit

2-Way Blow Ceiling Cassette





The PLFY-P-VLMD-E cassette unit fits into the space in a suspended ceiling to provide heating or cooling. This new unit has been redesigned with lower unit height and lower noise levels.



FEATURES

Grille Model Reference











CMP-63VLW-C

















INDOOR Heating Capacity (kW) (nominal) 8 Cooling Capacity (kW) (nominal) 7.1 8 High Performance Heating Capacity (kW) (UK) COP Priority Heating Capacity (kW) (UK) 7.5 Cooling Capacity (kW) (UK) 6.7 Cooling Capacity (Hi-Sens Mode) (kW) (UK) 5.2 0.7 SHF (UK) SHF (Hi-Sens Mode) (UK) 0.75 Heating Power Input (kW) (nominal) 0.094 Cooling Power Input (kW) (nominal) 0.101 Airflow (m³/min) - Lo-Mi-Hi 10 - 13 - 15.5 Sound Pressure Level (dBA) - Lo-Mi-Hi 32 - 37 - 39 Weight (kg) (Grille) 28 (7.5) Dimensions (mm) Width (Grille) 946 (1250) Dimensions (mm) Depth (Grille) 634 (710) Dimensions (mm) Height (Grille) 290 (20) Electrical Supply 220-240V, 50HZ SINGLE Running Current (A) - Heating / Cooling 0.43 / 0.49 Fuse Rating (BS88) - HRC (A) 6 Mains Cable No. Cores 3




PLFY-P63VLMD-E

Front View >





Side View >





 ϵ