## Air Conditioning

## **Product Information**

PQHY-P400YSHM-A: WY Series 16hp Water

**Cooled Unit** 

R410A Heat Pump





The WY Series has all the benefits of the Y Series using water cooled condensing units. It is also able to produce heat recovery via the water circuit between heat source units, making for a very economical system. Like the air source versions, the water cooled units benefit from a modular design approach. A twinning kit is required for double combinations.



## **FEATURES**











OUTDOOR	
Heating Capacity (kW) (nominal)	50
Cooling Capacity (kW) (nominal)	45
Heating Power Input (kW) (nominal)	8.65
Cooling Power Input (kW) (nominal)	8.25
COP / EER (nominal)	5.78 / 5.45
SCOP / SEER	5.67 / 5.86
Max No. of Connectable Indoor Units	34
Sound Pressure Level (dBA)	50
Sound Power Level (dBA)	64
Weight (kg)	195 + 195
Dimensions (mm) Width x Depth x Height	880 + 880 x 550 x 1160
Electrical Supply	380- 415V, 50HZ
Phase	3
Starting Current (A)	8/8
Running Current (A) - Heating	13.3
Running Current (A) - Cooling	12.7
Fuse Rating (BS88) - HRC (A)	20 / 20
Mains Cable No. Cores	4 + EARTH

Mains Cable No. Cores	4 + EARTH
PIPING RESTRICTIONS	
Total Piping Length (m)	500
Furthest Piping Length (m)	165
Furthest Piping Length After First Branch (m)	40
Between Indoor and Outdoor units - Height (m)	50
Between Indoor and Indoor units - Height (m)	15

## **DIMENSIONS**

PQHY-P400YSHM-A



