


# PUMY-P125VHM

Y Series 5hp Outdoor Unit

R410A Heat Pump



- A two core non-polar transmission line allows for simple installation of up to 8 indoor units
- The condensing unit is extremely slimline which allows easy location and application of the system



Pictures not to scale




## **Product Details**


PUMY-P125VHM	
Capacity (kW):	
Heating (Nominal)	16.0
Cooling (Nominal)	14.0
Heating (UK)	13.3
Cooling (UK)	12.9
Power Input (kW) Heating (Nominal)	4.33
Power Input (kW) Cooling (Nominal)	4.32
Power Input (kW) Heating (UK)	3.85
Power Input (kW) Cooling (UK)	3.66
Max No. of Connectable Indoor Units	8
Airflow (m3/min) (Heating / Cooling)	100 / 100
Noise (dBA) (Heating/ Cooling)	5250
Pipe Size Gas mm (in)	15.88 (5/8)
Pipe Size Liquid mm (in)	9.52 (3/8)
Width - mm	1350
Depth - mm	330 + 30
Height - mm	950
Weight - kg	127
Electrical Supply	220-240v, 50Hz
Phase	Single
Mains Cable No. Cores	3
Starting Current (A)	5
Running Current (A) - Heating	18.3
Running Current (A) - Cooling	18.3
Fuse Rating (BS88) - HRC (A)	40

Piping Restrictions	
Total Piping Length (m)	120
Furthest Piping Length (m)	80
Furthest Piping Length after 1st Branch (m)	30
Between Indoor and Outdoor Units - Height (m)	30
Between Indoor and Indoor Units - Height (m)	12

#### Dimension

### PUMY-P125VHM







Tel:

Fax:

## Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.





