


# PUMY-P140YHM

Y Series 6hp Outdoor Unit

R410A Heat Pump



- A two core non-polar transmission line allows for simple installation of up to 8 indoor units
- The condensing unit is extremely slimline which allows easy location and application of the system



Pictures not to scale




### **Product Details**


PUMY-P140YHM	
Capacity (kW):	
Heating (Nominal)	18.0
Cooling (Nominal)	15.5
Heating (UK)	14.9
Cooling (UK)	14.3
Power Input (kW) Heating (Nominal)	5.25
Power Input (kW) Cooling (Nominal)	5.1
Power Input (kW) Heating (UK)	4.7
Power Input (kW) Cooling (UK)	4.3
Max No. of Connectable Indoor Units	8
Airflow (m3/min) (Heating / Cooling)	100 / 100
Noise (dBA) (Heating/ Cooling)	5351
Pipe Size Gas mm (in)	15.88 (5/8)
Pipe Size Liquid mm (in)	9.52 (3/8)
Width - mm	950
Depth - mm	330+30
Height - mm	1350
Weight - kg	140
Electrical Supply	380-415v, 50Hz
Phase	3
Mains Cable No. Cores	4 +earth
Starting Current (A)	5
Running Current (A) - Heating	7.7
Running Current (A) - Cooling	7.5
Fuse Rating (BS88) - HRC (A)	16

Piping Restrictions	
Total Piping Length (m)	120
Furthest Piping Length (m)	80
Furthest Piping Length after 1st Branch (m)	30
Between Indoor and Outdoor Units - Height (m)	30
Between Indoor and Indoor Units - Height (m)	12

#### Dimension

## PUMY-P140YHM







## Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.



Tel:

Fax:



