Air Conditioning

Product Information PUMY-P100YHMB : Y Series 4hp Outdoor Unit R410A Heat Pump





The latest in Mitsubishi Electric Y Series technology incorporated within the new City Multi 4hp model allows up to 8 indoor units to be connected to a single outdoor unit, using the standard branch/header pipework system proven in the larger models. Utilising the latest Mitsubishi Electric Inverter technology, the system is fully controllable with all City Multi controllers or linked to third party BEMS.



FEATURES






OUTDOOR


OUIDOON	
Heating Capacity (kW) (nominal)	12.5
Cooling Capacity (kW) (nominal)	11.2
Heating Capacity (kW) (UK)	10.4
Cooling Capacity (kW) (UK)	10.3
Heating Power Input (kW) (nominal)	3.63
Cooling Power Input (kW) (nominal)	3.3
Heating Power Input (kW) (UK)	3.23
Cooling Power Input (kW) (UK)	2.81
COP / EER (nominal)	3.44 / 3.39
SCOP / SEER	3.4 / 5.2
Energy Efficiency Class - Heating / Cooling	A/A
Max No. of Connectable Indoor Units	8
Max Connectable Capacity	130%
Airflow (m ³ /min)	100
Pipe Size Gas (mm [in])	15.88 (5/8)
Pipe Size Liquid (mm ([in])	9.52 (3/8)
Sound Pressure Level (dBA)	49
Sound Power Level (dBA) Cooling	70
Weight (kg)	142
Dimensions (mm) Width x Depth x Height	950 x 330+30 x 1350
Electrical Supply	380-415V, 50HZ
Phase	3
Starting Current (A)	5
Running Current (A) - Heating	5.32
Running Current (A) - Cooling	4.84
Guaranteed Operating Range (°C) - Heating	-15 ~ 15
Guaranteed Operating Range (°C) - Cooling	-5 ~ 46
Fuse Rating (BS88) - HRC (A)	16
Mains Cable No. Cores	4+ EARTH
PIPING RESTRICTIONS	
Total Piping Length (m)	120
Furthest Piping Length (m)	80
Furthest Piping Length After First Branch (m)	30
Between Indoor and Outdoor units - Height (m)	50
Between Indoor and Indoor units - Height (m)	12

DIMENSIONS

PUMY-P100YHMB



Side View >





Telephone: 01707 282880 Fax: 01707 278881 Email: airconditioning@meuk.mee.com Website: http://www.airconditioning.mitsubishielectric.co.uk

Country of origin: United Kingdom – Japan – Thailand – Malaysia. © Mitsubishi Electric Europe 2013. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks of their respective owners.