Air Conditioning

Product Information

PURY-EP600YSKM-A: High COP R2 Series

24hp Outdoor UnitR410A Heat Recovery





Throughout the year, many buildings require cooling in some areas and heating in others - even in adjacent rooms. The outstanding City Multi R2 system meets this requirement by distributing surplus heat from cooling operations (and vice versa) to rooms where it is needed. This efficiency can result in energy savings of up to 30% over conventional systems.



FEATURES













Heating Capacity (kW) (nominal) Cooling Capacity (kW) (nominal) High Performance Heating Capacity (kW) (UK) COP Priority Heating Capacity (kW) (UK)	76.5 69 69.2 66.6 63.5 9.51
High Performance Heating Capacity (kW) (UK)	69.2 66.6 63.5
	66.6 63.5
COP Priority Heating Capacity (kW) (UK)	63.5
Cooling Capacity (kW) (UK)	9.51
Heating Power Input (kW) (nominal)	
Cooling Power Input (kW) (nominal)	7.07
High Performance Heating Power Input (kW) (UK)	9.46
COP Priority Heating Power Input (kW) (UK)	5.53
Cooling Power Input (kW) (UK)	0.67
COP / EER (nominal) 3.94 /	4.04
SCOP / SEER 5.41	/ 8.1
Max No. of Connectable Indoor Units	50
Airflow (m³/min) 320 +	320
Sound Pressure Level (dBA)	63
Sound Power Level (dBA)	83
Weight (kg) 322 +	322
Dimensions (mm) Width x Depth x Height 1750 + 1750 x 740 x	1710
Electrical Supply 380-415V, 5	0HZ
Phase	3
Starting Current (A)	8/8
Running Current (A) - Heating	30.1
Running Current (A) - Cooling	26.3
Fuse Rating (MCB sizes BS EN 60947-2) - (A) 25	/ 25
Mains Cable No. Cores 4 + EA	RTH

DIMENSIONS

PURY-EP600YSKM-A







