


PURY-RP200YJM-B

Replace Multi R2 Series 8hp Outdoor Unit R410A Heat Recovery



- Tried and tested technology that's been employed for over 5 years
- Efficient use of existing resources refrigerant piping, control and power wiring and less waste materials
- Reduced installation time with minimised disruption
- Ability to replace many non Mitsubishi Electric systems



Pictures not to scale




Product Details


PURY-RP200YJM-B	
Capacity (kW):	
Heating (Nominal)	25.0
Cooling (Nominal)	22.4
Heating (UK)	24.0
Cooling (UK)	21.1
Power Input (kW) Heating (Nominal)	5.5
Power Input (kW) Cooling (Nominal)	4.95
Power Input (kW) Heating (UK)	7.26
Power Input (kW) Cooling (UK)	3.61
Max No. of Connectable Indoor Units	20
Airflow(m3/min)	225
Noise (dBA)	56
Width - mm	1220
Depth - mm	760
Height - mm	1710
Weight - kg	275
Electrical Supply	380-415v, 50Hz
Phase	3
Mains Cable No. Cores	4 + earth
Starting Current (A)	8
Running Current (A) - Heating	8.9
Running Current (A) - Cooling	8
Fuse Rating (BS88) - HRC (A)	20


Piping Restrictions	
Total Piping Length (m)	220
Furthest Piping Length (m)	100
Between Outdoor and BC Controller - Length (m)	70
Between Indoor and BC Controller - Length (m)	30
Between Indoor and Outdoor Units - Height (m)	50
Between Indoor and BC Controller - Height (m)	15
Between Indoor and Indoor Units - Height (m)	15

Dimension

PURY-RP200YJM-B









Tel:

Fax:

Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.



