Air Conditioning

Product Information

PFFY-WP50VLRMM-EFloor Standing Concealed Indoor Unit (H-VRF)

Making a World of Difference

CITYMULTI



A compact concealed unit providing simple, effective air conditioning in perimeter zones. The unit is easy to install and at only 220mm deep offers an unobtrusive method of delivering highly efficient air-conditioning performance.

Key Features

- Reduced noise levels
- 3 static pressure settings 20/40/60Pa ideal for ducting in the perimeter zone
- Concealed unit for hidden installation. The unit can be hidden behind a wardrobe in a hotel, then ducted above and below the wardrobe doors this offers lower noise, less disruption and a low visual impact



Air Conditioning | Heating Ventilation | Controls



Air Conditioning

Product Information

PFFY-WP50VLRMM-E Floor Standing Concealed Indoor Unit (H-VRF)

Making a World of Difference


PFFY - IN	DOOR UNIT	PFFY-WP50VLRMM-E
CAPACITY (kW)	Heating (nominal)	6.3
	Cooling (nominal)	5.6
	UK Heating	6.3
	UK Total Cooling - Hi (Sensible)	5.00 (3.90)
	UK Total Cooling - Mi1	4.82
	UK Total Cooling - Lo	4.43
POWER INPUT (k	W) Heating (nominal)	0.07
	Cooling (nominal)	0.07
AIRFLOW (I/s)	Lo-Mi-Hi	175-217-250
EXTERNAL STATI	C PRESSURE (Pa)	20-40-60
SOUND PRESSU	RE LEVEL (dBA) Lo-Mi1-Hi	37-42-45
WEIGHT (kg)		29
DIMENSIONS (mr	n) Width	1246
	Depth	220
	Height	639
ELECTRICAL SUI	PPLY	220-240v, 50Hz
PHASE		Single
RUNNING CURRI	ENT (A) Heating / Cooling	0.65 / 0.65
FUSE RATING (BS	S88) - HRC (A)	6
MAINS CABLE No	o. Cores	3

H-VRF indoor units can only be configured with the CMB-WP HBC (H-VRF) and PURY-(E)P YLM-A or PQRY-P YLM outdoor units. Indoor unit water connections 3/4" BSP screw.



Dimensions

Model	Α	В	С	D	Е	F	G	① Water pipe (To HBC unit)	② Water pipe (From HBC unit)	
PFFY-WP20VLRMM-E	886	640	572	610	360	4	660			
PFFY-WP25VLRMM-E PFFY-WP32VLRMM-E	1006	760	692	730	480	5	780	100/4 30/0		
PFFY-WP40VLRMM-E PFFY-WP50VLRMM-E	1246	1000	932	970	720	7	1020			





Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division

Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)


Country of origin: unlead ringoom— augain — inleand— Masyasa. Antistudes leaders Europe 2.016. Missuesh and Missuesh is extend and readers are transmarkers of Missuesh is extended in the ringoom of the equipment described, or to withdrawn or replace products without prior notification or public amountainment. Missuishi Electric is constaintly developing and improving its products. All descriptors, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on equest. Third-party product and brand manes may be trade-so registered trademarks of their respective owners.













Mitsubishi Electric UK's commitment to the environment





