


Air Conditioning

Product Information

LGH-80RX5-E : LOSSNAY

Commercial Series



This commercially orientated system can be utilised virtually anywhere to extract stale air and then recover the heating or cooling energy to either warm or cool incoming fresh air.

FEATURES



LOSSNAY

Airflow (m³/h) - ExLo-Lo-Hi-ExHi	355-700-800-800
External Static Pressure (Pa) - ExLo-Lo-Hi-ExHi	20-95-120-150
Sound Pressure Level (dBA) Lossnay Ventilation - ExLo-Lo-Hi-ExHi	22-31-33-34.5
Sound Pressure Level (dBA) Bypass Ventilation - ExLo-Lo-Hi-ExHi	22-32-34-35.5
Electrical Supply	220-240V, 50HZ
Fuse Rating (BS88) - HRC (A)	6
Starting Current (A)	3.8
Running Current (A) - ExLo-Lo-Hi-ExHi	0.65-1.45-1.60-1.75
Power Input (W) - ExLo-Lo-Hi-ExHi	145-340-370-415
Temperature Exchange Efficiency (%) - ExLo-Lo-Hi-ExHi	87.5-80.5-79-79
Enthalpy Exchange Efficiency Heating (%) - ExLo-Lo-Hi-ExHi	79.5-72.5-?-?
Enthalpy Exchange Efficiency Cooling (%) - ExLo-Lo-Hi-ExHi	79.5-71.5-70-?
Dimensions (mm) - W-D-H	1004-1144-399
Weight (kg)	53
Duct Size (mm)	250

DIMENSIONS

LGH-80RX5-E

