Air Conditioning

Product Information MSZ-EF25VEB : Inverter Heat Pump R410A Wall Mounted System





The Zen Series is a wall mounted system that blends energy efficiency with a sophisticated, streamlined design. Combining an impressively low power consumption with a quiet, yet powerful performance, units have a distinctively styled front panel that not only looks appealing, but also helps to make cleaning of the unit easier. Designed to complement modern interior décor and suitable for a wide range of applications, Zen units blend in naturally wherever they are installed and are available in three striking colours; black, silver and white.



FEATURES





 \bigcirc

Heating Capacity (kW) (nominal) 3.2 (1.1 - 4.2 Cooling Capacity (kW) (nominal) 2.5 (1.2 - 3.4 Heating Capacity (kW) (UK) 2.48 (1.19 - 3.37 SHF (nominal and UK) 0.92 COO / EER (nominal) 4.57 / 4.56 SCOP / SEER 4.7 / 8.5 Energy Efficiency Class - Heating / Cooling A++ / A+++ Airflow (m ⁹ /min) (Heating) - Si-Lo-Mi-Hi-SupHi 4 - 4.6 - 6.2 - 8.9 - 11.5 Airflow (m ⁹ /min) (Cooling) - Si-Lo-Mi-Hi-SupHi 4 - 4.6 - 6.3 - 8.3 - 10.5 Pipe Size Gas (mm [in]) 9.52 (3/8 Pipe Size Liquid (mm (lin)) 6.35 (1/4 Sound Pressure Level (dBA) Heating - 21 - 24 - 29 - 37 - 45 Si-Lo-Mi-Hi-SupHi 21 - 23 - 29 - 36 - 42 Sound Pressure Level (dBA) Cooling - 21 - 23 - 29 - 36 - 42 Si-Lo-Mi-Hi-SupHi 895 x 195 x 295 Weight (kg) 11.5 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 2 Sound Pressure Level (dBA) Heating / Cooling 5 System Power Input (kW) - Heating / C		
Cooling Capacity (kW) (nominal) 2.5 (1.2 - 3.4) Heating Capacity (kW) (UK) 2.65 (0.91 - 3.49) Cooling Capacity (kW) (UK) 2.48 (1.19 - 3.37) SHF (nominal and UK) 0.92 COP / EER (nominal) 4.57 / 4.55 SCOP / SEER 4.7 / 8.5 Energy Efficiency Class - Heating / Cooling A++ / A++4 Airflow (m ³ /min) (Heating) - Si-Lo-Mi-Hi-SupHi 4 - 4.6 - 6.2 - 8.9 - 11.5 Airflow (m ³ /min) (Cooling) - Si-Lo-Mi-Hi-SupHi 4 - 4.6 - 6.3 - 8.3 - 10.5 Pipe Size Gas (mm [in]) 9.52 (3/8) Pipe Size Liquid (mm ([in]) 6.35 (1/4 Sound Pressure Level (dBA) Heating - 21 - 24 - 29 - 37 - 45 Si-Lo-Mi-Hi-SupHi 21 - 23 - 29 - 36 - 42 Sound Pressure Level (dBA) Cooling - 21 - 23 - 29 - 36 - 42 Si-Lo-Mi-Hi-SupHi 895 x 195 x 295 Weight (kg) 11.5 Dimensions (mm) Width x Depth x Height 895 x 195 x 295 Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR 30 Sound Pressure Level (dBA) Heating / Cooling 64 Dimensions (mm) Wid	INDOOR	
Heating Capacity (kW) (UK) 2.65 (0.91 - 3.49 Cooling Capacity (kW) (UK) 2.48 (1.19 - 3.77 SHF (nominal and UK) 0.92 COP / EER (nominal) 4.57 / 4.55 SCOP / SEER 4.7 / 8.5 Energy Efficiency Class - Heating / Cooling A++ / A+++ Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi 4 - 4.6 - 6.2 - 8.9 - 11.5 Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi 4 - 4.6 - 6.3 - 8.3 - 10.5 Pipe Size Gas (mm [in]) 9.52 (3/8 Pipe Size Liquid (mm (jin]) 6.35 (1/4 Sound Pressure Level (dBA) Heating - 21 - 24 - 29 - 37 - 45 Si-Lo-Mi-Hi-SupHi 21 - 23 - 29 - 36 - 42 Sound Pressure Level (dBA) Cooling - 21 - 23 - 29 - 36 - 42 Si-Lo-Mi-Hi-SupHi 895 x 195 x 295 Weight (kg) 11.5 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50HZ Phase SINGLE Sys	Heating Capacity (kW) (nominal)	3.2 (1.1 - 4.2)
Cooling Capacity (kW) (UK) 2.48 (1.19 - 3.37 SHF (nominal and UK) 0.92 COP / EER (nominal) 4.57 / 4.55 SCOP / SEER 4.7 / 8.5 Energy Efficiency Class - Heating / Cooling A++ / A+++ Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi 4 - 4.6 - 6.2 - 8.9 - 11.5 Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi 4 - 4.6 - 6.3 - 8.3 - 10.5 Pipe Size Gas (mm [in]) 9.52 (3/8) Pipe Size Liquid (mm ([in]) 6.35 (1/4 Sound Pressure Level (dBA) Heating - 21 - 24 - 29 - 37 - 45 Si-Lo-Mi-Hi-SupHi 21 - 23 - 29 - 36 - 42 Sound Pressure Level (dBA) Cooling - 21 - 23 - 29 - 36 - 42 Si-Lo-Mi-Hi-SupHi 895 x 195 x 295 Weight (kg) 11.5 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 Outdoor 26 Sound Pressure Level (dBA) Heating / Cooling 56 Weight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 <td< td=""><td>Cooling Capacity (kW) (nominal)</td><td>2.5 (1.2 - 3.4)</td></td<>	Cooling Capacity (kW) (nominal)	2.5 (1.2 - 3.4)
SHF (nominal and UK) 0.92 COP / EER (nominal) 4.57 / 4.55 SCOP / SEER 4.7 / 8.5 Energy Efficiency Class - Heating / Cooling A+++ / A++4 Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi 4 - 4.6 - 6.2 - 8.9 - 11.5 Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi 4 - 4.6 - 6.3 - 8.3 - 10.5 Pipe Size Gas (mm [in]) 9.52 (3/8) Pipe Size Gas (mm [in]) 9.52 (3/8) Pipe Size Liquid (mm (lin]) 6.35 (1/4) Sound Pressure Level (dBA) Heating - 21 - 23 - 29 - 36 - 42 Si-Lo-Mi-Hi-SupHi Sound Pressure Level (dBA) Cooling - Sound Pressure Level (dBA) Cooling - 21 - 23 - 29 - 36 - 42 Si-Lo-Mi-Hi-SupHi 895 x 195 x 295 Weight (kg) 11.5 Dimensions (mm) Width x Depth x Height 895 x 195 x 295 Weight (kg) 11.6 Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR 30 Sound Pressure Level (dBA) Heating / Cooling 56 Weight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50HZ	Heating Capacity (kW) (UK)	2.65 (0.91 - 3.49)
COP / EER (nominal) $4.57 / 4.55$ SCOP / SEER $4.7 / 8.5$ Energy Efficiency Class - Heating / Cooling $A++ / A++ A$ Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi $4 - 4.6 - 6.2 - 8.9 - 11.5$ Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi $4 - 4.6 - 6.3 - 8.3 - 10.5$ Pipe Size Gas (mm [in]) 9.52 (3/8Pipe Size Liquid (mm ([in]) 6.35 (1/4Sound Pressure Level (dBA) Heating - Si-Lo-Mi-Hi-SupHi $21 - 23 - 29 - 36 - 42$ Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi $21 - 23 - 29 - 36 - 42$ Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi $895 \times 195 \times 299$ Weight (kg) 11.5 Electrical SupplyFED BY OUTDOOR UNITPhaseSINGLEFuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores $48 / 47$ Sound Power Level (dBA) Cooling 56 Weight (kg) 30 Dimensions (mm) Width x Depth x Height $800 \times 285 \times 550$ Electrical SupplyFED BY OUTDOOR UNITPhaseSINGLESound Pressure Level (dBA) Cooling 56 Weight (kg) 30 Dimensions (mm) Width x Depth x Height $800 \times 285 \times 550$ Electrical Supply $220-240V$, 50HZPhaseSINGLESystem Power Input (kW) - Heating / Cooling $0.7 / 0.545$ (uK) $3.5 / 2.9 [7.3]$ Cooling <td>Cooling Capacity (kW) (UK)</td> <td>2.48 (1.19 - 3.37)</td>	Cooling Capacity (kW) (UK)	2.48 (1.19 - 3.37)
SCOP / SEER $4.7 / 8.5$ Energy Efficiency Class - Heating / Cooling $A++ / A++4$ Airflow (m³/min) (Leating) - Si-Lo-Mi-Hi-SupHi $4 - 4.6 - 6.2 - 8.9 - 11.5$ Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi $4 - 4.6 - 6.2 - 8.9 - 11.5$ Pipe Size Gas (mm [in]) 9.52 (3/8Pipe Size Liquid (mm ([in]) 6.35 (1/4Sound Pressure Level (dBA) Heating - Si-Lo-Mi-Hi-SupHi $21 - 23 - 29 - 37 - 45$ Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi $21 - 23 - 29 - 36 - 42$ Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi $895 \times 195 \times 295$ Weight (kg) 11.5 Electrical SupplyFED BY OUTDOOR UNITPhaseSINGLEFuse Rating (BS88) - HRC (A) 60 Interconnecting Cable No. Cores $48 / 47$ Sound Power Level (dBA) Heating / Cooling 56 OUTDOOR 56 Sound Pressure Level (dBA) Heating / Cooling 56 OUTDOOR 56 Sound Pressure Level (dBA) Heating / Cooling 56 Dimensions (mm) Width x Depth x Height $800 \times 285 \times 550$ Electrical Supply $220-240V$, 50HzPhaseSINGLESystem Power Input (kW) - Heating / Cooling $0.7 / 0.545$ System Power Input (kW) - Heating / Cooling $0.64 / 0.44$ (UK) $3.5 / 2.9$ [7.3Cooling 56 Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores $3.5 / 2.9$ [7.3Cooling 56 System Running Current (A) $3.5 / 2.9$ [7.3Cooling 56	SHF (nominal and UK)	0.92
Energy Efficiency Class - Heating / Cooling $A++ / A++ +$ Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi $4 - 4.6 - 6.2 - 8.9 - 11.5$ Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi $4 - 4.6 - 6.3 - 8.3 - 10.5$ Pipe Size Gas (mm [in]) 9.52 (3/8Pipe Size Liquid (mm ([in]) 6.35 (1/4Sound Pressure Level (dBA) Heating - Si-Lo-Mi-Hi-SupHi $21 - 24 - 29 - 37 - 45$ Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi $21 - 23 - 29 - 36 - 42$ Sound Pressure Level (dBA) Cooling - Dimensions (mm) Width x Depth x Height $895 \times 195 \times 295$ Weight (kg) 11.5 Electrical SupplyFED BY OUTDOOR UNITPhaseSINGLEFuse Rating (BS88) - HRC (A) 60 Dimensions (mm) Width x Depth x Height $800 \times 285 \times 550$ Sound Pressure Level (dBA) Heating / Cooling 56 OUTDOOR 56 Weight (kg) 30 Dimensions (mm) Width x Depth x Height $800 \times 285 \times 550$ Electrical Supply $220-240V$, 50H2PhaseSINGLESound Pressure Level (dBA) Heating / Cooling $0.7 / 0.545$ Meight (kg) 30 Dimensions (mm) Width x Depth x Height $800 \times 285 \times 550$ Electrical Supply $220-240V$, 50H2PhaseSINGLESystem Power Input (kW) - Heating / Cooling $0.7 / 0.545$ (nominal) 550 System Power Input (kW) - Heating / Cooling $0.64 / 0.44$ (UK) $3.5 / 2.9$ [7.3]Cooling 500 Fuse Rating (BS88) - HRC (A) 10 <	COP / EER (nominal)	4.57 / 4.59
Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi 4 - 4.6 - 6.2 - 8.9 - 11.5 Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi 4 - 4.6 - 6.3 - 8.3 - 10.5 Pipe Size Gas (mm [in]) 9.52 (3/8 Pipe Size Liquid (mm ([in]) 6.35 (1/4 Sound Pressure Level (dBA) Heating - 21 - 24 - 29 - 37 - 45 Si-Lo-Mi-Hi-SupHi Sound Pressure Level (dBA) Cooling - Sound Pressure Level (dBA) Cooling - 21 - 23 - 29 - 36 - 42 Si-Lo-Mi-Hi-SupHi 895 x 195 x 295 Weight (kg) 11.5 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR 30 Sound Pressure Level (dBA) Heating / Cooling 56 Meight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50H2 Phase SINGLE System Power Input (kW) - Heating / Cooling 0.7 / 0.545 (norminal) 0.7 / 0.545 System Power Input (kW) - Heating / Cooling 0.64 / 0.44 (UK) 3.5 / 2.9 [7.3	SCOP / SEER	4.7 / 8.5
Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi 4 - 4.6 - 6.3 - 8.3 - 10.5 Pipe Size Gas (mm [in]) 9.52 (3/8) Pipe Size Liquid (mm ([in]) 6.35 (1/4) Sound Pressure Level (dBA) Heating - 21 - 24 - 29 - 37 - 45 Sound Pressure Level (dBA) Cooling - 21 - 23 - 29 - 36 - 42 Sh-Lo-Mi-Hi-SupHi Sound Pressure Level (dBA) Cooling - Sound Pressure Level (dBA) Cooling 60 Dimensions (mm) Width x Depth x Height 895 x 195 x 295 Weight (kg) 11.5 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 61 Interconnecting Cable No. Cores 2 OUTDOOR 30 Sound Pressure Level (dBA) Heating / Cooling 48 / 47 Sound Pressure Level (dBA) Heating / Cooling 48 / 47 Sound Power Level (dBA) Cooling 56 UTDOOR 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50H2 Phase SINGLE System Power Input (kW) - Heating / Cooling 0.7 / 0.545 (norninal) 3.5 57 <	Energy Efficiency Class - Heating / Cooling	A++ / A+++
Pipe Size Gas (mm [in]) 9.52 (3/8 Pipe Size Liquid (mm ([in]) 6.35 (1/4 Sound Pressure Level (dBA) Heating - 21 - 24 - 29 - 37 - 45 Si-Lo-Mi-Hi-SupHi 21 - 23 - 29 - 36 - 42 Sound Pressure Level (dBA) Cooling - 21 - 23 - 29 - 36 - 42 Si-Lo-Mi-Hi-SupHi 895 x 195 x 295 Weight (kg) 11.5 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 2 OUTDOOR 30 Sound Pressure Level (dBA) Heating / Cooling 48 / 47 Sound Pressure Level (dBA) Heating / Cooling 48 / 47 Sound Pressure Level (dBA) Cooling 56 Weight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 555 Electrical Supply 220-240V, 50H2 Phase SINGLE System Power Input (kW) - Heating / Cooling 0.7 / 0.545 (norminal) 0.7 / 0.545 System Power Input (kW) - Heating / Cooling 0.64 / 0.44 (UK) 3.5 / 2.9 [7.3	Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi	4 - 4.6 - 6.2 - 8.9 - 11.9
Pipe Size Liquid (mm ([in])6.35 (1/4Sound Pressure Level (dBA) Heating - Si-Lo-Mi-Hi-SupHi21 - 24 - 29 - 37 - 45Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi21 - 23 - 29 - 36 - 42Sound Power Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi21 - 23 - 29 - 36 - 42Sound Power Level (dBA) Cooling60Dimensions (mm) Width x Depth x Height895 x 195 x 295Weight (kg)11.5Electrical SupplyFED BY OUTDOOR UNITPhaseSINGLEFuse Rating (BS88) - HRC (A)61Interconnecting Cable No. Cores2OUTDOOR30Sound Pressure Level (dBA) Heating / Cooling48 / 47Sound Power Level (dBA) Cooling56Weight (kg)30Dimensions (mm) Width x Depth x Height800 x 285 x 550Electrical Supply220-240V, 50H2PhaseSINGLESystem Power Input (kW) - Heating / Cooling (norminal)0.7 / 0.545System Power Input (kW) - Heating / Cooling (UK)0.64 / 0.44System Running Current (A)3.5System Running Current (A) [MAX] - Heating / Cooling3.5 / 2.9 [7.3Fuse Rating (BS88) - HRC (A)10Mains Cable No. Cores3	Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi	4 - 4.6 - 6.3 - 8.3 - 10.5
Sound Pressure Level (dBA) Heating - Si-Lo-Mi-Hi-SupHi Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi Sound Power Level (dBA) Cooling - Dimensions (mm) Width x Depth x Height By Si 195 x 299 - 36 - 42 Si-Lo-Mi-Hi-SupHi Sound Power Level (dBA) Cooling 60 Dimensions (mm) Width x Depth x Height Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 60 Interconnecting Cable No. Cores 7 OUTDOOR Sound Pressure Level (dBA) Heating / Cooling 78 Weight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling 0.7 / 0.545 (norminal) System Power Input (kW) - Heating / Cooling 0.64 / 0.42 (UK) Starting Current (A) 3.5 System Running Current (A) [MAX] - Heating / 3.5 / 2.9 [7.3] Cooling Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 32	Pipe Size Gas (mm [in])	9.52 (3/8)
Si-Lo-Mi-Hi-SupHi Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi Sound Power Level (dBA) Cooling 60 Dimensions (mm) Width x Depth x Height 895 x 195 x 299 Weight (kg) 11.5 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 61 Interconnecting Cable No. Cores 2 OUTDOOR Sound Pressure Level (dBA) Heating / Cooling 48 / 47 Sound Pressure Level (dBA) Cooling 56 Weight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling 0.7 / 0.544 (norminal) System Power Input (kW) - Heating / Cooling 0.64 / 0.44 (UK) 3.5 System Running Current (A) [MAX] - Heating / 3.5 / 2.9 [7.3 Cooling Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 3	Pipe Size Liquid (mm ([in])	6.35 (1/4)
Si-Lo-Mi-Hi-SupHi Sound Power Level (dBA) Cooling 60 Dimensions (mm) Width x Depth x Height 895 x 195 x 295 Weight (kg) 11.5 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 61 Interconnecting Cable No. Cores 2 OUTDOOR Sound Pressure Level (dBA) Heating / Cooling 48 / 47 Sound Pressure Level (dBA) Cooling 58 Weight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50H2 Phase SINGLE System Power Input (kW) - Heating / Cooling 0.7 / 0.545 (norminal) System Power Input (kW) - Heating / Cooling 0.64 / 0.44 (UK) 3.5 System Running Current (A) [MAX] - Heating / 3.5 / 2.9 [7.3 Cooling Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 3	Sound Pressure Level (dBA) Heating - Si-Lo-Mi-Hi-SupHi	21 - 24 - 29 - 37 - 45
Dimensions (mm) Width x Depth x Height 895 x 195 x 295 Weight (kg) 11.5 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR 48 / 47 Sound Pressure Level (dBA) Heating / Cooling 48 / 47 Sound Power Level (dBA) Cooling 56 Weight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 556 Electrical Supply 220-240V, 50H2 Phase SINGLE System Power Input (kW) - Heating / Cooling 0.7 / 0.545 (nominal) 0.54 / 0.44 System Power Input (kW) - Heating / Cooling 0.64 / 0.44 (UK) 3.5 5.9 System Running Current (A) 3.6 System Running Current (A) 3.5 System Running (BS88) - HRC (A) 10 Mains Cable No. Cores 3	Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi	21 - 23 - 29 - 36 - 42
Weight (kg) 11.2 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 2 OUTDOOR 48 / 47 Sound Pressure Level (dBA) Heating / Cooling 48 / 47 Sound Power Level (dBA) Cooling 56 Weight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50H2 Phase SINGLE System Power Input (kW) - Heating / Cooling 0.7 / 0.545 (IVK) 0.54 / 0.44 (UK) 3.5 System Running Current (A) 3.6 System Running Current (A) [MAX] - Heating / 3.5 / 2.9 [7.3 Cooling 588) - HRC (A) 10 Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 3	Sound Power Level (dBA) Cooling	60
Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR 48 / 47 Sound Pressure Level (dBA) Heating / Cooling 48 / 47 Sound Pressure Level (dBA) Cooling 56 Weight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 0.7 / 0.545 System Power Input (kW) - Heating / Cooling 0.64 / 0.44 (UK) 3.5 System Running Current (A) 3.5 System Running Current (A) [MAX] - Heating / 3.5 / 2.9 [7.3] Cooling 5888) - HRC (A) 10 Mains Cable No. Cores 3	Dimensions (mm) Width x Depth x Height	895 x 195 x 299
Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR 48 / 47 Sound Pressure Level (dBA) Heating / Cooling 48 / 47 Sound Power Level (dBA) Cooling 56 Weight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50H2 Phase SINGLE System Power Input (kW) - Heating / Cooling 0.7 / 0.545 (nominal) 0.54 / 0.44 (UK) 3.5 / 2.9 [7.3] System Running Current (A) 3.5 / 2.9 [7.3] Cooling 588) - HRC (A) 10 Mains Cable No. Cores 3.5	Weight (kg)	11.5
Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR 48 / 47 Sound Pressure Level (dBA) Heating / Cooling 48 / 47 Sound Power Level (dBA) Cooling 58 Weight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50H2 Phase SINGLE System Power Input (kW) - Heating / Cooling 0.7 / 0.545 (IVK) 0.54 / 0.44 (UK) 3.5 System Power Input (kW) - Heating / Cooling 0.56 / 0.44 (IVR) 3.5 System Running Current (A) 3.5 System Running Current (A) [MAX] - Heating / 3.5 / 2.9 [7.3] Cooling 5 Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 3	Electrical Supply	FED BY OUTDOOR UNIT
Interconnecting Cable No. Cores 4 OUTDOOR Sound Pressure Level (dBA) Heating / Cooling 48 / 47 Sound Power Level (dBA) Cooling 58 Weight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50H2 Phase SINGLE System Power Input (kW) - Heating / Cooling 0.7 / 0.545 (nominal) System Power Input (kW) - Heating / Cooling 0.64 / 0.44 (UK) Starting Current (A) 3.5 System Running Current (A) [MAX] - Heating / 3.5 / 2.9 [7.3 Cooling Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 3	Phase	SINGLE
OUTDOOR Sound Pressure Level (dBA) Heating / Cooling 48 / 47 Sound Power Level (dBA) Cooling 56 Weight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50H2 Phase SINGLE System Power Input (kW) - Heating / Cooling 0.7 / 0.545 (nominal) 0.64 / 0.44 System Power Input (kW) - Heating / Cooling 0.64 / 0.44 (UK) 3.5 System Running Current (A) 3.5 System Running Current (A) [MAX] - Heating / 3.5 / 2.9 [7.3 Cooling 5 Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 3	Fuse Rating (BS88) - HRC (A)	6
Sound Pressure Level (dBA) Heating / Cooling 48 / 47 Sound Power Level (dBA) Cooling 58 Weight (kg) 36 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50H2 Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 0.7 / 0.545 System Power Input (kW) - Heating / Cooling 0.64 / 0.44 (UK) 3.5 System Running Current (A) 3.5 System Running Current (A) [MAX] - Heating / 3.5 / 2.9 [7.3] Cooling 10 Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 3	Interconnecting Cable No. Cores	4
Sound Power Level (dBA) Cooling 58 Weight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 0.7 / 0.545 System Power Input (kW) - Heating / Cooling 0.64 / 0.44 (UK) 3.5 System Running Current (A) 3.5 System Running Current (A) [MAX] - Heating / 3.5 / 2.9 [7.3 Cooling 548 Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 3.5	OUTDOOR	
Weight (kg) 30 Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50H2 Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 0.7 / 0.545 System Power Input (kW) - Heating / Cooling 0.64 / 0.44 (UK) 3.5 System Running Current (A) 3.5 System Running Current (A) [MAX] - Heating / 3.5 / 2.9 [7.3 Cooling 5 Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 3	Sound Pressure Level (dBA) Heating / Cooling	48 / 47
Dimensions (mm) Width x Depth x Height 800 x 285 x 550 Electrical Supply 220-240V, 50H2 Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 0.7 / 0.545 System Power Input (kW) - Heating / Cooling 0.64 / 0.44 (UK) 0.64 / 0.44 System Running Current (A) 3.5 System Running Current (A) [MAX] - Heating / 3.5 / 2.9 [7.3 Cooling 10 Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 3	Sound Power Level (dBA) Cooling	58
Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 0.7 / 0.545 System Power Input (kW) - Heating / Cooling 0.64 / 0.44 (UK) Starting Current (A) 3.5 System Running Current (A) [MAX] - Heating / Cooling 3.5 / 2.9 [7.3 Cooling Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 3	Weight (kg)	30
Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 0.7 / 0.545 (nominal) System Power Input (kW) - Heating / Cooling 0.64 / 0.44 (UK) 2 Starting Current (A) 3.5 System Running Current (A) [MAX] - Heating / Cooling 3.5 / 2.9 [7.3 Cooling Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 3	Dimensions (mm) Width x Depth x Height	800 x 285 x 550
System Power Input (kW) - Heating / Cooling 0.7 / 0.545 (nominal) System Power Input (kW) - Heating / Cooling 0.64 / 0.44 (UK) Starting Current (A) 3.5 System Running Current (A) [MAX] - Heating / 3.5 / 2.9 [7.3 Cooling Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 3	Electrical Supply	220-240V, 50HZ
(nominal) System Power Input (kW) - Heating / Cooling (UK) Starting Current (A) System Running Current (A) [MAX] - Heating / Cooling Fuse Rating (BS88) - HRC (A) Mains Cable No. Cores	Phase	SINGLE
(UK) Starting Current (A) 3.5 System Running Current (A) [MAX] - Heating / 3.5 / 2.9 [7.3 Cooling Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores	System Power Input (kW) - Heating / Cooling (nominal)	0.7 / 0.545
System Running Current (A) [MAX] - Heating / 3.5 / 2.9 [7.3 Cooling Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 3	System Power Input (kW) - Heating / Cooling (UK)	0.64 / 0.44
Cooling Fuse Rating (BS88) - HRC (A) 10 Mains Cable No. Cores 3	Starting Current (A)	3.5
Mains Cable No. Cores	System Running Current (A) [MAX] - Heating / Cooling	3.5 / 2.9 [7.3]
	Fuse Rating (BS88) - HRC (A)	10
Max Pipe Length (m) 20	Mains Cable No. Cores	з
	Max Pipe Length (m)	20

DIMENSIONS


MSZ-EF25VEB

P

AUTO


HOIAN


REPLACE



E.


貧





DIMENSIONS

MUZ-EF25VE



Front View >

550

12

0.8 (7)

280

22.3

10

150

302.5

500 Bolt pitch for installation 800

Side View > 23 32° ° 164.5 32 99.5 170.5

j≏e 8e

69



Max Height Difference (m)

Charge R410A (kg) - (pre charged length)

CE

Telephone: 01707 282880 Fax: 01707 278881 Email: airconditioning@meuk.mee.com Website: http://www.airconditioning.mitsubishielectric.co.uk

Country of origin: United Kingdom – Japan – Thailand – Malaysia.

Mitsubishi Electric Europe 2013. Mitsubishi and Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks of their respective owners.