Air Conditioning

Product Information

MSZ-EF Zen Inverter Heat Pump Wall Mounted System Making a World of Difference

M series



MSZ-EF Zen Inverter Heat Pump

The Zen Series is a wall mounted system that blends energy efficiency with a sophisticated, streamlined design.



Air Conditioning | Heating Ventilation | Controls Combining an impressively low power consumption with a quiet, yet powerful performance, units have a distinctively styled front panel that not only looks appealing, but also helps to make cleaning of the unit easier

Designed to complement modern interior décor and suitable for a wide range of applications, Zen units blend in naturally wherever they are installed and are available in three striking colours; black, silver and white.

Key Features

- New stylish design
- Energy efficient operation
- Quiet operation
- Weekly Timer
- Nano Platinum filter
- Recognised by the Noise Abatement Society for industry leading low noise levels
- Replace Technology available
- Multi-Split compatibility
- Compatible with City Multi when used in conjuction with PAC-LV11M LEV kit

Product Information

Air Conditioning

. 16 - 2

MSZ-EF Zen Inverter Heat Pump Wall Mounted System Making a World of Difference



MSZ-EF - INDOOR UNITS		MSZ-EF25VE2-B/S/W	MSZ-EF35VE2-B/S/W	MSZ-EF50VE2-B/S/W
CAPACITY (kW)	Heating (nominal)	3.2 (1.1-4.2)	4.0 (1.8-5.5)	5.8 (1.6-7.5)
	Cooling (nominal)	2.5 (1.2-3.4)	3.5 (1.4-4.0)	5.0 (1.4-5.4)
	Heating (UK)	2.65 (0.91-3.49)	3.32 (1.5-4.57)	4.82 (1.33-6.23)
	Cooling (UK)	2.48 (1.19-3.37)	3.47 (1.38-3.97)	4.96 (1.39-5.36)
SHF (nominal)		0.92	0.80	0.71
COP / EER (nominal)		4.57 / 4.59	4.19 / 3.85	3.71 / 3.21
SCOP / SEER (BSEN14825)		4.7 / 8.5	4.6 / 8.5	4.5 / 7.2
ErP ENERGY EFFICIENCY CLASS Heating/Cooling		A++ / A+++	A++ / A+++	A+ / A++
AIRFLOW (m ³ /min)	Heating/Cooling - SLo-Lo-Mi-Hi-Shi	4.0-4.6-6.2-8.9-11.9 / 4.0-4.6-6.3-8.3-10.5	4.0-4.6-6.2-8.9-12.7 / 4.0-4.6-6.3-8.3-10.5	6.4-7.3-9.0-11.1-13.2/5.8-6.8-7.9-9.3-11.0
PIPE SIZE mm (in)	Gas	9.52 (3/8")	9.52 (3/8")	12.7 (1/2")
	Liquid	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
SOUND PRESSURE LEVEL (dBA) Heating/Cooling - Silent-Lo-Mi-Hi-Shi		21-24-29-37-45 / 21-23-29-36-42	21-24-30-38-46 / 21-24-29-36-42	30-33-37-43-49 / 30-33-36-40-43
SOUND POWER LEVEL (dBA)		60	60	60
DIMENSIONS (mm)	Width x Depth x Height	895 x 195 x 299	895 x 195 x 299	895 x 195 x 299
WEIGHT (kg)		11.5	11.5	11.5
ELECTRICAL SUPPLY		Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit
FUSE RATING (BS88) – HRC (A)		6	6	6
INTERCONNECTING CABLE No. CORES		4	4	4

 $\mathsf{B}=\mathsf{Black} \quad \mathsf{S}=\mathsf{Silver} \quad \mathsf{W}=\mathsf{White}$

MUZ-EF - OUTDOOR UNITS		MUZ-EF25VE	MUZ-EF35VE	MUZ-EF50VE
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		48 / 47	50 / 49	52 / 52
SOUND POWER LEVEL (dBA) Cooling		58	61	65
WEIGHT (kg)		30	35	54
DIMENSIONS (mm)	Width x Depth x Height	800 x 285 x 550	800 x 285 x 550	840 x 330 x 880
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
PHASE		Single	Single	Single
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	0.700 / 0.545	0.955 / 0.910	1.565 / 1.560
	Heating/Cooling (UK)	0.64 / 0.44	0.87 / 0.73	1.42 / 1.25
STARTING CURRENT (A)		3.5	4.4	7
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		3.5 / 2.9 [7.3]	4.4 / 4.2 [8.5]	7.0 / 6.9 [12.4]
FUSE RATING (BS88) – HRC (A)		10	10	16
MAINS CABLE No. CORES		3	3	3
MAX PIPE LENGTH (m)		20	20	30
MAX HEIGHT DIFFERENCE (m)		12	12	15
CHARGE R410A (kg) - 7m		0.8	1.15	1.45



Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division

Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland

Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom – Japan – Thaland – Malaysia. (Mitsubish) Electric Europe 2014. Mitsubish) Electric are trademarks of Mitsubish Electric Europe B.V. The company reserves the right to make any variation in technical specification to the enginement described, or to withdraw or replace products without prior moltification or public announcement. Mitsubish Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's Seneral Conditions of bala, a coop of which is available on request. Third-party product and brand rames may be trademarks or registred trademarks of their respective owners.





Mitsubishi Electric UK's commitment to the environment



in , Connect with Green Gateway

