# Air Conditioning

Product Information MSZ-EF35VES : Inverter Heat Pump R410A Wall Mounted System





The Zen Series is a wall mounted system that blends energy efficiency with a sophisticated, streamlined design. Combining an impressively low power consumption with a quiet, yet powerful performance, units have a distinctively styled front panel that not only looks appealing, but also helps to make cleaning of the unit easier. Designed to complement modern interior décor and suitable for a wide range of applications, Zen units blend in naturally wherever they are installed and are available in three striking colours; black, silver and white.



#### FEATURES





INDOOR	
Heating Capacity (kW) (nominal)	4 (1.8 - 5.5)
Cooling Capacity (kW) (nominal)	3.5 (1.4 - 4)
Heating Capacity (kW) (UK)	3.32 (1.5 - 4.57)
Cooling Capacity (kW) (UK)	3.47 (1.38 - 3.97)
SHF (nominal and UK)	0.8
COP / EER (nominal)	4.19 / 3.85
SCOP / SEER	4.6 / 8.5
Energy Efficiency Class - Heating / Cooling	A++ / A+++
Airflow (m <sup>3</sup> /min) (Heating) - Si-Lo-Mi-Hi-SupHi	4 - 4.6 - 6.2 - 8.9 - 11.9
Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi	4 - 4.6 - 6.3 - 8.3 - 10.5
Pipe Size Gas (mm [in])	9.52 (3/8)
Pipe Size Liquid (mm ([in])	6.35 (1/4)
Sound Pressure Level (dBA) Heating - Si-Lo-Mi-Hi-SupHi	21 - 24 - 30 - 38 - 46
Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi	21 - 23 - 29 - 36 - 42
Sound Power Level (dBA) Cooling	60
Dimensions (mm) Width x Depth x Height	895 x 195 x 299
Weight (kg)	11.5
Electrical Supply	FED BY OUTDOOR UNIT
Phase	SINGLE
Fuse Rating (BS88) - HRC (A)	6
Interconnecting Cable No. Cores	4
OUTDOOR	
Sound Pressure Level (dBA) Heating / Cooling	50 / 49
Sound Power Level (dBA) Cooling	61
Weight (kg)	35
Dimensions (mm) Width x Depth x Height	800 x 285 x 550
Electrical Supply	220-240V, 50HZ
Phase	SINGLE
System Power Input (kW) - Heating / Cooling (nominal)	0.955 / 0.91
System Power Input (kW) - Heating / Cooling (UK)	0.87 / 0.73
Starting Current (A)	4.4
System Running Current (A) [MAX] - Heating / Cooling	4.4 / 4.2 [8.5]
Fuse Rating (BS88) - HRC (A)	10
Mains Cable No. Cores	3
May Dina Langth (m)	20

### DIMENSIONS


AUTO


HOLAN

REPLACE



**P** 





I.

貧



Side View >

#### DIMENSIONS


47

MUZ-EF35VE

20


12

1.15 (7)



Front View >

iew > \_\_\_\_\_\_ 22.3 \_\_\_



## 

Max Pipe Length (m)

Max Height Difference (m)

Charge R410A (kg) - (pre charged length)

CE

#### Telephone: 01707 282880 Fax: 01707 278881 Email: airconditioning@meuk.mee.com Website: http://www.airconditioning.mitsubishielectric.co.uk

Country of origin: United Kingdom – Japan – Thailand – Malaysia. 

Mitsubishi Electric Europe 2013. Mitsubishi and Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks of their respective owners.