Air Conditioning

Product Information

MSZ-SF50VE: Inverter Heat Pump

R410A Wall Mounted System





These models offer industry leading noise levels and have a distinctively styled front panel that not only looks appealing, but also helps to make cleaning of the unit easier.





FEATURES

































Heating Capacity (kW) (nominal) 5.8 (1.4 - 7.4) Cooling Capacity (kW) (uK) 4.8 (1.16 - 6.06) Cooling Capacity (kW) (UK) 4.8 (1.16 - 6.06) Cooling Capacity (kW) (UK) 4.96 (1.38 - 5.35) SHF (nominal and UK) 0.7 COP / EER (nominal) 3.41 / 3.01 SCOP / SEER 4.47 / 2. Energy Efficiency Class - Heating / Cooling A+ / A++ Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi 5.6 - 6.4 - 8 - 9.8 - 12 Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi 5.6 - 6.2 - 7 - 8.2 - 9.9 Pipe Size Gas (mm [in]) 6.35 (1/4) Sound Pressure Level (dBA) Heating - 30 - 33 - 38 - 43 - 49 Si-Lo-Mi-Hi-SupHi 30 - 33 - 38 - 40 - 45 Si-Lo-Mi-Hi-SupHi 5.8 Sound Possure Level (dBA) Cooling - 30 - 33 - 36 - 40 - 45 Si-Lo-Mi-Hi-SupHi 798 x 195 x 299 Weight (kg) 10 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR 52 / 52 <t< th=""><th>INDOOR</th><th></th></t<>	INDOOR	
Heating Capacity (kW) (UK)	Heating Capacity (kW) (nominal)	5.8 (1.4 - 7.3)
Cooling Capacity (kW) (UK) 4.96 (1.38 - 5.35) SHF (nominal and UK) 0.7 COP / EER (nominal) 3.41 / 3.01 SCOP / SEER 4.4 / 7.2 Energy Efficiency Class - Heating / Cooling A+ / A++ Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi 5.6 - 6.4 - 8 - 9.8 - 12 Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi 5.6 - 6.2 - 7 - 8.2 - 9.9 Pipe Size Gas (mm [in]) 12.7 (1/2) Pipe Size Liquid (mm ([in]) 6.35 (1/4) Sound Pressure Level (dBA) Heating - 30 - 33 - 38 - 43 - 49 Si-Lo-Mi-Hi-SupHi 30 - 33 - 36 - 40 - 45 Sound Pressure Level (dBA) Cooling - 30 - 33 - 36 - 40 - 45 Si-Lo-Mi-Hi-SupHi 798 x 195 x 299 Weight (kg) 10 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR 5 Sound Pressure Level (dBA) Heating / Cooling 52 / 52 Sound Power Level (dBA) Cooling 6 Weight (kg) 5 Dimensions (mm) Width x	Cooling Capacity (kW) (nominal)	5 (1.4 - 5.4)
SHF (nominal and UK) 0.7 COP / EER (nominal) 3.41 / 3.01 SCOP / SEER 4.4 / 7.2 Energy Efficiency Class - Heating / Cooling A+ / A++ Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi 5.6 - 6.4 - 8 - 9.8 - 12 Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi 5.6 - 6.2 - 7 - 8.2 - 9.9 Pipe Size Gas (mm [in]) 12.7 (1/2) Pipe Size Liquid (mm ([in]) 6.35 (1/4) Sound Pressure Level (dBA) Heating - Si-Lo-Mi-Hi-SupHi 30 - 33 - 38 - 43 - 49 Si-Lo-Mi-Hi-SupHi 30 - 33 - 36 - 40 - 45 Si-Lo-Mi-Hi-SupHi 30 - 33 - 36 - 40 - 45 Si-Lo-Mi-Hi-SupHi 798 x 195 x 299 Weight (kg) 10 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR 55 Sound Power Level (dBA) Heating / Cooling 55 Sound Power Level (dBA) Cooling 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50Hz Ph	Heating Capacity (kW) (UK)	4.8 (1.16 - 6.06)
COP / SEER 3.41 / 3.01 SCOP / SEER 4.4 / 7.2 Energy Efficiency Class - Heating / Cooling A+ / A++ Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi 5.6 - 6.4 - 8 - 9.8 - 12 Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi 5.6 - 6.2 - 7 - 8.2 - 9.9 Pipe Size Gas (mm [in]) 12.7 (1/2) Pipe Size Liquid (mm ([in]) 6.35 (1/4) Sound Pressure Level (dBA) Heating - Si-Lo-Mi-Hi-SupHi 30 - 33 - 38 - 43 - 49 Si-Lo-Mi-Hi-SupHi 30 - 33 - 36 - 40 - 45 Si-Lo-Mi-Hi-SupHi 798 x 195 x 299 Weight (kg) 10 Dimensions (mm) Width x Depth x Height 798 x 195 x 299 Weight (kg) 10 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR 55 Sound Power Level (dBA) Heating / Cooling 55 Sound Power Level (dBA) Cooling 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50Hz Phase </td <td>Cooling Capacity (kW) (UK)</td> <td>4.96 (1.38 - 5.35)</td>	Cooling Capacity (kW) (UK)	4.96 (1.38 - 5.35)
SCOP / SEER 4.4 / 7.2 Energy Efficiency Class - Heating / Cooling A+ / A++ Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi 5.6 - 6.4 - 8 - 9.8 - 12 Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi 5.6 - 6.2 - 7 - 8.2 - 9.9 Pipe Size Gas (mm [in]) 12.7 (1/2) Pipe Size Liquid (mm (lin]) 6.35 (1/4) Sound Pressure Level (dBA) Heating - Si-Lo-Mi-Hi-SupHi 30 - 33 - 38 - 43 - 49 Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi 30 - 33 - 36 - 40 - 45 Sound Power Level (dBA) Cooling 58 Dimensions (mm) Width x Depth x Height 798 x 195 x 299 Weight (kg) 10 Electrical Supply FED BY OUTDOOR UNIT Phase Sund Pressure Level (dBA) Heating / Cooling 52 / 52 Sound Pressure Level (dBA) Cooling 55 Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50Hz Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.75 / 1.66 System Power Input (kW) - Heating / Cooling (UK) 7.6 / 7.4 [12.3]	SHF (nominal and UK)	0.7
A+ / A++ Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi 5.6 - 6.4 - 8 - 9.8 - 12 Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi 5.6 - 6.2 - 7 - 8.2 - 9.9 Pipe Size Gas (mm [in]) 12.7 (1/2) Pipe Size Liquid (mm (lin]) 6.35 (1/4) Sound Pressure Level (dBA) Heating - 30 - 33 - 38 - 43 - 49 Si-Lo-Mi-Hi-SupHi Sound Pressure Level (dBA) Cooling - 30 - 33 - 36 - 40 - 45 Si-Lo-Mi-Hi-SupHi Sound Power Level (dBA) Cooling - 30 - 33 - 36 - 40 - 45 Si-Lo-Mi-Hi-SupHi Sound Power Level (dBA) Cooling - 58 Dimensions (mm) Width x Depth x Height 798 x 195 x 299 Weight (kg)	COP / EER (nominal)	3.41 / 3.01
Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi 5.6 - 6.4 - 8 - 9.8 - 12 Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi 5.6 - 6.2 - 7 - 8.2 - 9.9 Pipe Size Gas (mm [in]) 12.7 (1/2) Pipe Size Liquid (mm ([in]) 6.35 (1/4) Sound Pressure Level (dBA) Heating - Si-Lo-Mi-Hi-SupHi 30 - 33 - 38 - 43 - 49 Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi 30 - 33 - 36 - 40 - 45 Sound Power Level (dBA) Cooling 58 Dimensions (mm) Width x Depth x Height 798 x 195 x 299 Weight (kg) 10 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR 52 / 52 Sound Pressure Level (dBA) Heating / Cooling 55 Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 System Power Input (kW) - Heating / Cooling (nominal) 7.6 / 7.4 [12.3] System Running Current (A) 7.6 / 7.4 [12.3]	SCOP / SEER	4.4 / 7.2
Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi	Energy Efficiency Class - Heating / Cooling	A+ / A++
Pipe Size Gas (mm [in]) 12.7 (1/2) Pipe Size Liquid (mm ([in]) 6.35 (1/4) Sound Pressure Level (dBA) Heating - Si-Lo-Mi-Hi-SupHi 30 - 33 - 38 - 43 - 49 Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi 30 - 33 - 36 - 40 - 45 Sound Power Level (dBA) Cooling 58 Dimensions (mm) Width x Depth x Height 798 x 195 x 299 Weight (kg) 10 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR Sound Power Level (dBA) Heating / Cooling 52 / 52 Sound Power Level (dBA) Cooling 65 Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 System Power Input (kW) - Heating / Cooling 1.55 / 1.34 (UK) 3 3 System Running Current (A) 7.6 / 7.4 [12.3] Cooling <td>Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi</td> <td>5.6 - 6.4 - 8 - 9.8 - 12</td>	Airflow (m³/min) (Heating) - Si-Lo-Mi-Hi-SupHi	5.6 - 6.4 - 8 - 9.8 - 12
Pipe Size Liquid (mm ([in]) 6.35 (1/4) Sound Pressure Level (dBA) Heating - Si-Lo-Mi-Hi-SupHi 30 - 33 - 38 - 43 - 49 Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi 30 - 33 - 36 - 40 - 45 Sound Power Level (dBA) Cooling 58 Dimensions (mm) Width x Depth x Height 798 x 195 x 299 Weight (kg) 10 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR 55 Sound Power Level (dBA) Heating / Cooling 52 / 52 Sound Power Level (dBA) Cooling 65 Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 System Power Input (kW) - Heating / Cooling (nominal) 7.6 / 7.4 [12.3] Cooling 1.55 / 1.34 Euse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (Airflow (m³/min) (Cooling) - Si-Lo-Mi-Hi-SupHi	5.6 - 6.2 - 7 - 8.2 - 9.9
Sound Pressure Level (dBA) Heating - Si-Lo-Mi-Hi-SupHi Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi Sound Power Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi Sound Power Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi Sound Power Level (dBA) Cooling - Si-BD Dimensions (mm) Width x Depth x Height - Si-BD SX x 195 x 299 Weight (kg) - Si-BD SY OUTDOOR UNIT Phase - SINGLE Fuse Rating (BS88) - HRC (A) - Interconnecting Cable No. Cores - OUTDOOR Sound Pressure Level (dBA) Heating / Cooling - Sound Power Level (dBA) Coo	Pipe Size Gas (mm [in])	12.7 (1/2)
Si-Lo-Mi-Hi-SupHi Sound Pressure Level (dBA) Cooling - Si-Lo-Mi-Hi-SupHi Sound Power Level (dBA) Cooling 58 Dimensions (mm) Width x Depth x Height 798 x 195 x 299 Weight (kg) 10 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR Sound Pressure Level (dBA) Heating / Cooling 52 / 52 Sound Power Level (dBA) Cooling 65 Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) System Power Input (kW) - Heating / Cooling (nominal) System Power Input (kW) - Heating / Cooling (nominal) System Running Current (A) [MAX] - Heating / Cooling Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	Pipe Size Liquid (mm ([in])	6.35 (1/4)
Si-Lo-Mi-Hi-SupHi 58 Sound Power Level (dBA) Cooling 58 Dimensions (mm) Width x Depth x Height 798 x 195 x 299 Weight (kg) 10 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR Sound Pressure Level (dBA) Heating / Cooling 52 / 52 Sound Power Level (dBA) Cooling 65 Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 System Power Input (kW) - Heating / Cooling (UK) 7.6 Starting Current (A) 7.6 System Running Current (A) [MAX] - Heating / Cooling 7.6 / 7.4 [12.3] Cooling 7.6 / 7.4 [12.3] Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) <td>The state of the s</td> <td>30 - 33 - 38 - 43 - 49</td>	The state of the s	30 - 33 - 38 - 43 - 49
Dimensions (mm) Width x Depth x Height 798 x 195 x 299 Weight (kg) 10 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR Sound Pressure Level (dBA) Heating / Cooling 52 / 52 Sound Power Level (dBA) Cooling 65 Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 System Power Input (kW) - Heating / Cooling (UK) 7.6 / 7.4 [12.3] Cooling 1.55 / 1.34 Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15		30 - 33 - 36 - 40 - 45
Weight (kg) 10 Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR Sound Pressure Level (dBA) Heating / Cooling 52 / 52 Sound Power Level (dBA) Cooling 65 Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 System Power Input (kW) - Heating / Cooling (UK) 7.6 / 7.4 [12.3] System Running Current (A) [MAX] - Heating / Cooling 7.6 / 7.4 [12.3] Cooling 1.55 / 1.34 Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	Sound Power Level (dBA) Cooling	58
Electrical Supply FED BY OUTDOOR UNIT Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR Sound Pressure Level (dBA) Heating / Cooling 52 / 52 Sound Power Level (dBA) Cooling 65 Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 System Power Input (kW) - Heating / Cooling (UK) 7.6 / 7.4 [12.3] System Running Current (A) [MAX] - Heating / Cooling 7.6 / 7.4 [12.3] Cooling 7.6 / 7.4 [12.3] Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	Dimensions (mm) Width x Depth x Height	798 x 195 x 299
Phase SINGLE Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR Sound Pressure Level (dBA) Heating / Cooling 52 / 52 Sound Power Level (dBA) Cooling 65 Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 System Power Input (kW) - Heating / Cooling (UK) 7.6 / 7.4 [12.3] Cooling 7.6 / 7.4 [12.3] Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	Weight (kg)	10
Fuse Rating (BS88) - HRC (A) 6 Interconnecting Cable No. Cores 4 OUTDOOR Sound Pressure Level (dBA) Heating / Cooling 52 / 52 Sound Power Level (dBA) Cooling 65 Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 (nominal) System Power Input (kW) - Heating / Cooling (UK) 7.6 / 7.4 [12.3] System Running Current (A) [MAX] - Heating / Cooling 7.6 / 7.4 [12.3] Cooling 1.5 / 7.4 [12.3] Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	Electrical Supply	FED BY OUTDOOR UNIT
OUTDOOR 4 Sound Pressure Level (dBA) Heating / Cooling 52 / 52 Sound Power Level (dBA) Cooling 65 Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 System Power Input (kW) - Heating / Cooling (UK) 7.6 / 7.4 [12.3] System Running Current (A) [MAX] - Heating / Cooling 7.6 / 7.4 [12.3] Cooling 1 Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	Phase	SINGLE
OUTDOOR Sound Pressure Level (dBA) Heating / Cooling 52 / 52 Sound Power Level (dBA) Cooling 65 Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 System Power Input (kW) - Heating / Cooling (UK) 7.6 Starting Current (A) 7.6 System Running Current (A) [MAX] - Heating / Cooling 7.6 / 7.4 [12.3] Cooling 16 Fuse Rating (BS88) - HRC (A) 16 Main Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	Fuse Rating (BS88) - HRC (A)	6
Sound Pressure Level (dBA) Heating / Cooling 52 / 52 Sound Power Level (dBA) Cooling 65 Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 System Power Input (kW) - Heating / Cooling (UK) 7.6 / 7.4 [12.3] System Running Current (A) [MAX] - Heating / Cooling 7.6 / 7.4 [12.3] Cooling 1.55 / 1.34 Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	Interconnecting Cable No. Cores	4
Sound Power Level (dBA) Cooling 65 Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 System Power Input (kW) - Heating / Cooling (UK) 7.6 Starting Current (A) 7.6 System Running Current (A) [MAX] - Heating / Cooling 7.6 / 7.4 [12.3] Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	OUTDOOR	
Weight (kg) 55 Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 (nominal) System Power Input (kW) - Heating / Cooling (UK) 7.6 Starting Current (A) 7.6 System Running Current (A) [MAX] - Heating / Cooling 7.6 / 7.4 [12.3] Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	Sound Pressure Level (dBA) Heating / Cooling	52 / 52
Dimensions (mm) Width x Depth x Height 840 x 330 x 880 Electrical Supply 220-240V, 50HZ Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 System Power Input (kW) - Heating / Cooling (UK) 7.5 / 1.34 Starting Current (A) 7.6 / 7.4 [12.3] Cooling Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	Sound Power Level (dBA) Cooling	65
Phase SINGLE	Weight (kg)	55
Phase SINGLE System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 System Power Input (kW) - Heating / Cooling (UK) 1.55 / 1.34 Starting Current (A) 7.6 System Running Current (A) [MAX] - Heating / Cooling 7.6 / 7.4 [12.3] Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	Dimensions (mm) Width x Depth x Height	840 x 330 x 880
System Power Input (kW) - Heating / Cooling (nominal) 1.7 / 1.66 System Power Input (kW) - Heating / Cooling (UK) 1.55 / 1.34 Starting Current (A) 7.6 System Running Current (A) [MAX] - Heating / Cooling 7.6 / 7.4 [12.3] Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	Electrical Supply	220-240V, 50HZ
(nominal) System Power Input (kW) - Heating / Cooling (UK) 1.55 / 1.34 (UK) Starting Current (A) 7.6 System Running Current (A) [MAX] - Heating / Cooling 7.6 / 7.4 [12.3] Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	Phase	SINGLE
(UK) 7.6 Starting Current (A) 7.6 System Running Current (A) [MAX] - Heating / Cooling 7.6 / 7.4 [12.3] Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	,	1.7 / 1.66
System Running Current (A) [MAX] - Heating / Cooling 7.6 / 7.4 [12.3] Fuse Rating (BS88) - HRC (A) 16 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15		1.55 / 1.34
Cooling 16 Fuse Rating (BS88) - HRC (A) 3 Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15	Starting Current (A)	7.6
Mains Cable No. Cores 3 Max Pipe Length (m) 30 Max Height Difference (m) 15		7.6 / 7.4 [12.3]
Max Pipe Length (m) 30 Max Height Difference (m) 15	Fuse Rating (BS88) - HRC (A)	16
Max Height Difference (m) 15	Mains Cable No. Cores	3
	Max Pipe Length (m)	30
Charge R410A (kg) - (pre charged length) 1.55 (7)	Max Height Difference (m)	15
	Charge R410A (kg) - (pre charged length)	1.55 (7)

DIMENSIONS

MSZ-SF25_50










DIMENSIONS

MUZ-SF25_50









 ϵ