



Power Inverter Heat Pump

R410A Ceiling Suspended System

Advanced inverter technology makes the Mr Slim Power Inverter the number one choice for improving comfort. They provide energy savings of up to 70% annually when compared to a previous non-inverter model. Operating noise has also been reduced thanks to improvements in fan design, while existing pipe work is reusable for easier maintenance and installation.

- Indoor unit designed for direct ceiling suspension
- Flush to wall installation for concealment of service connections







Pictures not to scale

Product Details

PCA-RP60KAQ Indoor Unit	
Capacity (kW):	
Heating (Nominal) (Low - High)	7.00 (2.80 - 8.20)
Cooling (Nominal) (Low - High)	6.00 (2.70 - 6.70)
Heating (UK) (Low - High)	5.95 (2.40 - 6.95)
Cooling (UK) (Low - High)	5.50 (2.50 - 6.15)
SHF R410A (Nominal)	0.81
COP / EER (Nominal)	3.61 / 4
Energy Label Heating / Cooling	A / A
Width - mm	1280
Depth - mm	680
Height - mm	230
Weight - kg	32
Airflow (m3/min) - Lo-Mi1-Mi2-Hi	15-16-17-19
Noise (dBA) - Lo-Mi1-Mi2-Hi	33-35-37-40
Pipe Size Gas mm (in)	15.88 (5/8)
Pipe Size Liquid mm (in)	9.52 (3/8)
Electrical Supply	Fed by Outdoor Unit
Phase	Single
Fuse Rating (BS88) - HRC (A)	6
Interconnecting Cable No. Cores	4

PUHZ-R Width - m Depth - m Height - m Weight - k Noise (dB Electrical Phase Fuse Rati SystemPo SystemPo SystemPo

PUHZ-RP60VHA4 Outdoor Unit	
Width - mm	950
Depth - mm	330 + 30
Height - mm	943
Weight - kg	67
Noise (dBA) (Heating /Cooling) - Lo-Hi	48 /44-47
Electrical Supply	220-240v, 50Hz
Phase	Single
Fuse Rating (BS88) - HRC (A)	25
SystemPower Input (kW) - Heating (Nominal)	1.94
SystemPower Input (kW) - Cooling (Nominal)	1.5
SystemPower Input (kW) - Heating (UK)	1.73
SystemPower Input (kW) - Cooling (UK)	1.28
SystemRunning Current (A) - Heating / Cooling	8.82 / 6.84
Mains Cable No. Cores	3
Max Pipe Length (m)	50

Dimensions

PCA-RP60KAQ


Front View >




100

hast


C2360




Lower View >



UHZ-RP60VHA4





Right Side View >





Telephone: 01707 282880

30

3.5

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.





Max Height Difference (m)

Charge (kg) - 30m