Air Conditioning

Product Information

PCA-RP100KAQ (Three Phase)
Power Inverter Heat Pump
Ceiling Suspended System

Making a World of Difference



Our wide range of Power Inverters offer customers high seasonal efficiency, advanced control options and quiet operation, whilst providing greater flexibility and ease of installation.

Key Features

- Stylish indoor unit designed for direct ceiling suspension
- Flush to wall installation for concealment of service connections
- Automatic air speed adjustment
- High/low ceiling height modes





Air Conditioning | Heating Ventilation | Controls



Product Information

PCA-RP100KAQ (Three Phase) **Power Inverter Heat Pump** Ceiling Suspended System

Making a World of Difference

Air Conditioning

PCA-RP - INDOOR UNITS		PCA-RP100KAQ
CAPACITY (kW)	Heating (nominal)	11.2 (4.5-14.0)
	Cooling (nominal)	9.5 (4.9-11.4)
	Heating (UK)	9.5 (3.85-11.9)
	Cooling (UK)	9.2 (4.5-10.5)
SHF (nominal & UK)		0.77
COP / EER (nominal)		3.68 / 3.93
SCOP / SEER (BS EN14825)		3.9 / 5.9
ErP ENERGY EFFICIENCY CLASS Heating/Cooling		A / A+
AIRFLOW (I/s)	Lo-Mi1-Mi2-Hi	367-400-433-467
PIPE SIZE mm (in)	Gas/Liquid	15.88 (5/8") / 9.52 (3/8")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi1-Mi2-Hi	37-39-41-43
SOUND POWER LEVEL (dBA)		63
DIMENSIONS (mm)	Width x Depth x Height	1600 x 680 x 230
WEIGHT (kg)		36
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6
INTERCONNECTING CABLE No. Cores		4

PUHZ-ZRP - OUTDOOR UNITS		PUHZ-ZRP100YKA2 3 Three Phase
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		51 / 49
SOUND POWER LEVEL (dBA) Cooling		69
WEIGHT (kg)		123
DIMENSIONS (mm)	Width x Depth x Height	1050 x 330 + 40 x 1338
ELECTRICAL SUPPLY		380-415v, 50Hz
PHASE		Three
SYSTEM POWER	Heating/Cooling (nominal)	3.04 / 2.42
INPUT (kW)	Heating/Cooling (UK)	2.16 / 2.08
STARTING CURRENT (A)		4.0
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		4.07 / 4.04 [8.7]
FUSE RATING (BS88) - HRC (A)		16
MAINS CABLE No. Cores		5
MAX PIPE LENGTH (m)		75
MAX HEIGHT DIFFERENCE (m)		30
CHARGE R410A (kg) - 30m		5.0


3 Three Phase

Note: High efficiency filter is optional



DIMENSIONS


Front View



Upper View



Back View





Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland

of origin: United Kingdom – Japan – Thailand – Malaysia. ©Mitsubishi Bectric Europe 2015. Mitsubishi and Mitsubishi Bectric are trademarks of Mitsubish Bectric Europe B.V. The company reserves the alea any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing viring its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to sany's General Conditions of Sale, a copy of which is available on request. Third-party product and brand mems may be trademarks or registered trademarks of their respective owners.










Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)





Mitsubishi Electric UK's commitment to the environment





