Air Conditioning

Product Information

PCA-RP60KAQ (Single Phase) Power Inverter Heat Pump Ceiling Suspended System

Making a World of Difference

mr.slim.



Our wide range of Power Inverters offer customers high seasonal efficiency, advanced control options and quiet operation, whilst providing greater flexibility and ease of installation.

Key Features

- Stylish indoor unit designed for direct ceiling suspension
- Flush to wall installation for concealment of service connections
- Automatic air speed adjustment
- High/low ceiling height modes





Air Conditioning | Heating Ventilation | Controls



Product Information

PCA-RP60KAQ (Single Phase) Power Inverter Heat Pump Ceiling Suspended System

Air intake

Air outlet

DIMENSIONS

Making a World of Difference

380 - 57

54

85

88 95 230


182

PCA-RP - INDOOR UNITS		PCA-RP60KAQ
CAPACITY (kW)	Heating (nominal)	7.0 (2.8-8.2)
	Cooling (nominal)	6.0 (2.7-6.7)
	Heating (UK)	5.95 (2.4-6.95)
	Cooling (UK)	5.5 (2.5-6.15)
SHF (nominal & UK)		0.81
COP / EER (nominal)		3.63 / 3.67
SCOP / SEER (BS EN14825)		4.3 / 6.2
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	A+ / A++
AIRFLOW (I/s)	Lo-Mi1-Mi2-Hi	250-267-283-317
PIPE SIZE mm (in)	Gas/Liquid	15.88 (5/8") / 9.52 (3/8")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi1-Mi2-Hi	33-35-37-40
SOUND POWER LEVEL (dBA)		60
DIMENSIONS (mm)	Width x Depth x Height	1280 x 680 x 230
WEIGHT (kg)		32
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6
INTERCONNECTING CABLE No. Cores		4

Air Conditioning

PUHZ-ZRP - OUTDOOR UNITS		PUHZ-ZRP60VHA
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		48 / 47
SOUND POWER LEVEL (dBA) Cooling		67
WEIGHT (kg)		67
DIMENSIONS (mm)	Width x Depth x Height	950 x 330 + 30 x 943
ELECTRICAL SUPPLY		220-240v, 50Hz
PHASE		Single
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	1.93 / 1.66
	Heating/Cooling (UK)	1.72 / 1.41
STARTING CURRENT (A)		5.0
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		9.26 / 8.07 [19.4]
FUSE RATING (BS88) - HRC (A)		25
MAINS CABLE No. Cores		3
MAX PIPE LENGTH (m)		50
MAX HEIGHT DIFFERENCE (m)		30
CHARGE R410A (kg) - 30m		2.4

Note: High efficiency filter is optional



Back View

Front View

1198

Upper View

1280 1173





Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division

Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom – Japan – Thaland – Malaysia. @Mitsubishi Electric Europe 2015. Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prive notification or public amouncement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sala, a copy of which is available on request. Third-parky product and brand manes may be trademarks or registred trademarks of their respective owners.



Mitsubishi Electric UK's commitment to the environment



You mitsubishielectric2

Note: The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and side specific conditions. Misubish Electrics air conditioning and heat yoump systems contain fluorinated greenhouse gases N410A, N407C and R134a.