# Air Conditioning

## **Product Information**

PEAD-RP100JAQ: Standard Inverter Heat

**Pump** 

R410A Ceiling Concealed Ducted System









### **FEATURES**






























INDOOR	
Heating Capacity (kW) (nominal)	11.2 (4.5 - 12.5)
Cooling Capacity (kW) (nominal)	9.4 (4.9 - 11.2)
Heating Capacity (kW) (UK)	9.5 (3.85 - 10.65)
Cooling Capacity (kW) (UK)	8.65 (4.5 - 10.3)
SHF (nominal and UK)	0.85
COP / EER (nominal)	3.61 / 3.01
SCOP / SEER	3.8 / 4.6
Energy Efficiency Class - Heating / Cooling	A/B
Airflow (m³/min) Lo-Mi-Hi	24 - 29 - 34
Pipe Size Gas (mm [in])	15.88 (5/8")
Pipe Size Liquid (mm ([in])	9.52 (3/8")
External Static Pressure (Pa) Lo-Mi-Mi2-Mi3-Hi	35 - 50 - 70 - 100 - 150
Sound Pressure Level (dBA) Lo-Mi-Hi	29 - 34 - 38
Sound Power Level (dBA) Cooling	61
Dimensions (mm) Width x Depth x Height	1400 x 732 x 250
Weight (kg)	41
Electrical Supply	FED BY OUTDOOR UNIT
Phase	SINGLE
Fuse Rating (BS88) - HRC (A)	6
Interconnecting Cable No. Cores	4

Interconnecting Cable No. Cores	4
OUTDOOR	
Sound Pressure Level (dBA) Heating / Cooling	54 / 50
Sound Power Level (dBA) Cooling	70
Weight (kg)	75
Dimensions (mm) Width x Depth x Height	950 x (330+30) x 943
Electrical Supply	220-240V, 50HZ
Phase	SINGLE
System Power Input (kW) - Heating / Cooling (nominal)	3.10 / 3.12
System Power Input (kW) - Heating / Cooling (UK)	2.76 / 2.58
Starting Current (A)	12
System Running Current (A) [MAX] - Heating / Cooling	16.27 / 15.55 [30.7]
Fuse Rating (BS88) - HRC (A)	32
Mains Cable No. Cores	3
Max Pipe Length (m)	50
Max Height Difference (m)	30
Charge R410A (kg) - Pre charged length (m)	3 - 30


### **DIMENSIONS**

PEAD-RP100JAQ



### **DIMENSIONS**

PUHZ-P100VHA4





 $\epsilon$