



PKA-RP50FAL2

Power Inverter Heat Pump

R410A Wall Mounted System

Advanced inverter technology makes the Mr Slim Power Inverter the number one choice for improving comfort. They provide energy savings of up to 70% annually when compared to a previous non-inverter model. Operating noise has also been reduced thanks to improvements in fan design, while existing pipe work is reusable for easier maintenance and installation.

- **Adjustable louvres for uniform air distribution**
- **Internal pipe connection to wall mounted unit for easy and neat installation**



Pictures not to scale

Product Details

PKA-RP50FAL2 Indoor Unit


Capacity (kW):	
Heating (Nominal) (Low - High)	6.00 (2.50 - 7.30)
Cooling (Nominal) (Low - High)	5.00 (2.30 - 5.60)
Heating (UK) (Low - High)	5.10 (2.15 - 6.20)
Cooling (UK) (Low - High)	4.50 (2.05 - 5.05)
SHF R410A (Nominal)	0.86
COP / EER (Nominal)	3.41 / 3.01
Energy Label Heating / Cooling	B / B
Width - mm	1400
Depth - mm	235
Height - mm	340
Weight - kg	24
Airflow (m ³ /min) - Lo-Hi	15-20
Noise (dBA) - Lo-Hi	39-45
Pipe Size Gas mm (in)	12.7 (1/2)
Pipe Size Liquid mm (in)	6.35 (1/4)
Electrical Supply	Fed by outdoor unit
Phase	Single
Fuse Rating (BS88) - HRC (A)	6
Interconnecting Cable No. Cores	4

PUHZ-RP50VHA2 Outdoor Unit


Width - mm	800
Depth - mm	300 + 23
Height - mm	600
Weight - kg	45
Noise (dBA) (Heating / Cooling)	46 / 44
Electrical Supply	220-240v, 50Hz
Phase	Single
Fuse Rating (BS88) - HRC (A)	16
System Power Input (kW) - Heating (Nominal)	1.76
System Power Input (kW) - Cooling (Nominal)	1.66
System Power Input (kW) - Heating (UK)	1.57
System Power Input (kW) - Cooling (UK)	1.41
Starting Current (A)	5
System Running Current (A) - Heating / Cooling	6.9 / 6.59
Mains Cable No. Cores	3
Max Pipe Length (m)	50
Max Height Difference (m)	30
Charge (kg) - 30m	2.5

Dimensions

PKA-RP50FAL2



PUHZ-RP50VHA2



Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: <http://www.mitsubishielectric.co.uk/aircon>

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.

Tel:
Fax:

