Air Conditioning

Product Information PKA-RP60KAL : Power Inverter Heat Pump R410A Wall Mounted System





Our wide range of power inverters offer customers high seasonal efficiency, advanced control options and quiet operation, whilst providing greater flexibility and ease of installation.



FEATURES


















Heating capacity (kW) (nominal)	7.0 (2.8 - 8.2)
Cooling Capacity (kW) (nominal)	6 (2.7 - 6.7)
Heating Capacity (kW) (UK)	6.0 (2.4 - 6.95)
Cooling Capacity (kW) (UK)	5.5 (2.5 - 6.15)
SHF (nominal and UK)	0.86
COP/EER (nominal)	3.57 / 3.81
SCOP / SEER	4.2 / 6.3
Energy Efficiency Class - Heating / Cooling	A+ / A++
Airflow (m³/min) Lo-Mi-Hi	18 - 20 - 22
Pipe Size Gas (mm [in])	15.88 (5/8")
Pipe Size Liquid (mm ([in])	9.52 (3/8")
Sound Pressure Level (dBA) Lo-Mi-Hi	39 - 42 - 45
Sound Power Level (dBA) Cooling	64
Dimensions (mm) Width x Depth x Height	1170 x 295 x 365
Weight (kg)	21
Electrical Supply	FED BY OUTDOOR UNIT
Phase	SINGLE
Fuse Rating (BS88) - HRC (A)	6
Interconnecting Cable No. Cores	4
OUTDOOR	
Sound Pressure Level (dBA) Heating / Cooling	48 / 47
Sound Power Level (dBA) Cooling	67
Weight (kg)	67
Weight (kg) Dimensions (mm) Width x Depth x Height	
	67 950 x (330+30) x 943 220-240V, 50HZ
Dimensions (mm) Width x Depth x Height	950 x (330+30) x 943 220-240V, 50HZ
Dimensions (mm) Width x Depth x Height Electrical Supply	950 x (330+30) x 943
Dimensions (mm) Width x Depth x Height Electrical Supply Phase System Power Input (kW) - Heating / Cooling	950 x (330+30) x 943 220-240V, 50HZ SINGLE
Dimensions (mm) Width x Depth x Height Electrical Supply Phase System Power Input (kW) - Heating / Cooling (nominal) System Power Input (kW) - Heating / Cooling (UK)	950 x (330+30) x 943 220-240V, 50HZ SINGLE 1.96 / 1.60 1.42 / 1.67
Dimensions (mm) Width x Depth x Height Electrical Supply Phase System Power Input (kW) - Heating / Cooling (nominal) System Power Input (kW) - Heating / Cooling	950 x (330+30) x 943 220-240V, 50HZ SINGLE 1.96 / 1.60
Dimensions (mm) Width x Depth x Height Electrical Supply Phase System Power Input (kW) - Heating / Cooling (nominal) System Power Input (kW) - Heating / Cooling (UK) Starting Current (A) System Running Current (A) [MAX] - Heating /	950 x (330+30) x 943 220-240V, 50HZ SINGLE 1.96 / 1.60 1.42 / 1.67 5 9.23 / 8.11 [19.4]
Dimensions (mm) Width x Depth x Height Electrical Supply Phase System Power Input (kW) - Heating / Cooling (nominal) System Power Input (kW) - Heating / Cooling (UK) Starting Current (A) System Running Current (A) [MAX] - Heating / Cooling	950 x (330+30) x 943 220-240V, 50HZ SINGLE 1.96 / 1.60 1.42 / 1.67
Dimensions (mm) Width x Depth x Height Electrical Supply Phase System Power Input (kW) - Heating / Cooling (nominal) System Power Input (kW) - Heating / Cooling (UK) Starting Current (A) System Running Current (A) [MAX] - Heating / Cooling Fuse Rating (BS88) - HRC (A)	950 x (330+30) x 943 220-240V, 50HZ SINGLE 1.96 / 1.60 1.42 / 1.67 5 9.23 / 8.11 [19.4] 25

DIMENSIONS

PKA-RP60KAL

Front View >


Side View >






DIMENSIONS

PUHZ-ZRP60VHA



Right Side View >



673

#431 #447



CE

Telephone: 01707 282880 Fax: 01707 278881 Email: airconditioning@meuk.mee.com Website: http://www.airconditioning.mitsubishielectric.co.uk

473

Country of origin: United Kingdom – Japan – Thailand – Malaysia.

Mitsubishi Electric Europe 2013. Mitsubishi and Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks of their respective owners.