



PLA-RP35BA

Power Inverter Heat Pump

R410A 4-Way Blow Ceiling Cassette System

Advanced inverter technology makes the Mr Slim Power Inverter the number one choice for improving comfort. They provide energy savings of up to 70% annually when compared to a previous non-inverter model. Operating noise has also been reduced thanks to improvements in fan design, while existing pipe work is reusable for easier maintenance and installation.

- **Airflow controllable for ceiling heights up to 4.2m, with automatic adjustment of fan speed**
- **Reduced draft air distribution, with independent vane control**
- **Filter lowering operation down to 4m (optional PLP-6BAJ grille required)**
- **Optional 'I See Sensor' for energy saving and smooth temperature control throughout the room**



Pictures not to scale

Product Details	
Product Name	Advanced Analytics Dashboard
Version	2.1.0
Release Date	2023-10-27
Category	Software
Manufacturer	ABC Corp.
SKU	PROD-12345
Weight	0.5 kg
Dimensions	10 x 10 x 5 cm
Material	Aluminum
Color	Black
Features	Real-time data processing, Customizable views, API integration
Usage Instructions	See user manual for detailed instructions.
Warranty	1 Year
Support	24/7 Customer Support
Price	\$199.99
Availability	In Stock

PLA-RP35BA Indoor Unit

Capacity (kW):	
Heating (Nominal) (Low - High)	4.10 (1.60 - 5.20)
Cooling (Nominal) (Low - High)	3.60 (1.60 - 4.50)
Heating (UK) (Low - High)	3.50 (1.35 - 4.40)
Cooling (UK) (Low - High)	3.25 (1.45 - 4.05)
SHF R410A (Nominal)	0.84
COP / EER (Nominal)	3.66 / 3.36
Energy Label Heating / Cooling	A / A
Width (grille) - mm	840 (950)
Depth (grille) - mm	840 (950)
Height (grille) - mm	258 (35)
Weight (grille) - kg	22 (6)
Airflow (m3/min) - Lo-Mi1-Mi2-Hi	11-12-13-15
Noise (dBA) - Lo-Mi1-Mi2-Hi	27-28-29-31
Pipe Size Gas mm (in)	12.7 (1/2)
Pipe Size Liquid mm (in)	6.35 (1/4)
Electrical Supply	Fed by Outdoor Unit
Phase	
Fuse Rating (BS88) - HRC (A)	6
Interconnecting Cable No. Cores	4
Grille Ref	PLP-6BA GRILLE
Remote Controller Ref	PAR-21MAA

PUHZ-RP35VHA3 Outdoor Unit

Width - mm	800
Depth - mm	300 + 23
Height - mm	600
Weight - kg	42
Noise (dBA) (Heating /Cooling)	46 /44
Electrical Supply	220-240v, 50Hz
Phase	Single
Fuse Rating (BS88) - HRC (A)	16
SystemPower Input (kW) - Heating (Nominal)	1.12
SystemPower Input (kW) - Cooling (Nominal)	1.07
SystemPower Input (kW) - Heating (UK)	1
SystemPower Input (kW) - Cooling (UK)	0.91
SystemRunning Current (A) - Heating / Cooling	5.02 / 4.8
Mains Cable No. Cores	3
Max Pipe Length (m)	50
Max Height Difference (m)	30
Charge (kg) - 30m	2.5



Telephone: 01707 282880
Email: air.conditioning@meuk.mee.com Website: <http://www.mitsubishielectric.co.uk/aircon>

Email: air.conditioning@meuk.mee.com Website: <http://www.mitsubishielectric.co.uk/aircon>




Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.

Tel:
Fax:



Dimensions

PLA-RP35BA



PUHZ-RP35VHA3

