

Air Conditioning

Product Information

PLA-ZRP Zubadan Inverter Heat Pump
4-Way Blow Ceiling Cassette System

Making a
World of
Difference

Mr.SLIM.



PLA-ZRP Zubadan Inverter Heat Pump

4-Way Blow Ceiling Cassette System

The Mr Slim Zubadan Inverter heat pumps achieve an excellent heating performance even when the outdoor air temperature is as low as -25°C and can also maintain full heating capacity at -15°C .

Key Features

- Swing Vane Mode with Auto Vane Shutter
- Auto-Restart
- Quiet operation
- 72 different airflow patterns - 2, 3 or 4 way discharge
- High ceiling compatibility through wide flow air outlets
- Auto-Changeover
- Hot Start - draught prevention
- Factory charged refrigerant up to 30m
- Long-life filter with optional high efficiency filter also available
- Drain lift pump as standard
- Fresh air knockout
- Ceiling soiling prevention
- Replace Technology available
- Refrigerant volume check function
- Optional I-See Sensor
- Duty Standby Operation
- Optional Demand Control
- Optional Noise Reduction

 **MITSUBISHI
ELECTRIC**
LIVING ENVIRONMENTAL SYSTEMS

Air Conditioning | Heating
Ventilation | Controls

Air Conditioning

Product Information

PLA-ZRP Zubadan Inverter Heat Pump 4-Way Blow Ceiling Cassette System

Making a
World of
Difference



ZUBADAN

PLA-ZRP - INDOOR UNITS		PLA-ZRP71BA	PLA-ZRP100BA	PLA-ZRP100BA	PLA-ZRP125BA
CAPACITY (kW)	Heating (nominal)	8.0 (4.5-10.2)	11.2 (4.5-14.0)	11.2 (4.5-14.0)	14.0 (5.0-16.0)
	Cooling (nominal)	7.1 (4.9-8.1)	10.0 (4.9-11.4)	10.0 (4.9-11.4)	12.5 (5.5-14.0)
	Heating (UK)	6.8 (3.9-8.65)	9.5 (3.85-11.9)	9.5 (3.85-11.9)	11.9 (4.25-13.6)
	Cooling (UK)	6.55 (4.5-7.45)	9.2 (4.5-10.5)	9.2 (4.5-10.5)	11.5 (5.05-12.9)
SHF (nominal & UK)		0.85	0.74	0.74	0.74
COP / EER (nominal)		3.91 / 3.81	4.20 / 3.59	4.20 / 3.59	3.61 / 2.81
SCOP / SEER (BSEN14825)		3.7 / 5.1	4.0 / 5.5	4.0 / 5.5	3.5 / 5.1
EP ENERGY EFFICIENCY CLASS	Heating/Cooling	A / A	A+ / A	A+ / A	A / A
AIRFLOW (m³/min)	Lo-Mi1-Mi2-Hi	17-19-21-23	20-23-26-30	20-23-26-30	22-25-28-31
PIPE SIZE mm (in)	Gas/Liquid	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi1-Mi2-Hi	28-30-34-36	32-34-37-40	32-34-37-40	34-36-39-41
SOUND POWER LEVEL (dBA)		58	65	65	66
DIMENSIONS (mm)	Width x Depth x Height (Grille)	840 (950) x 840 (950) x 258 (35)	840 (950) x 840 (950) x 298 (35)	840 (950) x 840 (950) x 298 (35)	840 (950) x 840 (950) x 298 (35)
WEIGHT (kg)	Unit / Panel	25 / 6	26 / 6	26 / 6	27 / 6
ELECTRICAL SUPPLY		Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6	6	6	6
INTERCONNECTING CABLE No. Cores		4	4	4	4
GRILLE REFERENCE		PLP-6BA	PLP-6BA	PLP-6BA	PLP-6BA
WIRED REMOTE CONTROLLER REFERENCE		PAR-31MAA	PAR-31MAA	PAR-31MAA	PAR-31MAA

PUHZ-SHW - OUTDOOR UNITS		PUHZ-SHW80VHA	PUHZ-SHW112VHA	PUHZ-SHW112YHA ^③ Three Phase	PUHZ-SHW140YHA ^③ Three Phase
SOUND PRESSURE LEVEL (dBA)	Heating/Cooling	51 / 50	52 / 51	52 / 51	52 / 51
SOUND POWER LEVEL (dBA)	Cooling	68	69	69	69
WEIGHT (kg)		120	120	134	134
DIMENSIONS (mm)	Width x Depth x Height	950 x 330 + 30 x 1350	950 x 330 + 30 x 1350	950 x 330 + 30 x 1350	950 x 330 + 30 x 1350
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz	380-415,50Hz	380-415,50Hz
PHASE		Single	Single	Three	Three
SYSTEM POWER	Heating/Cooling (nominal)	2.047 / 1.864	2.677 / 2.786	2.677 / 2.786	3.879 / 4.449
INPUT (kW)	Heating/Cooling (UK)	1.82 / 1.58	2.37 / 2.37	2.37 / 2.37	3.45 / 3.78
STARTING CURRENT (A)		14	14	3	3
SYSTEM RUNNING CURRENT (A)	Heating/Cooling [MAX]	9.35 / 8.54 [30.2]	11.94 / 11.84 [35.8]	4.40 / 4.43 [13.8]	5.62 / 5.72 [14.1]
FUSE RATING (BS88) - HRC (A)		32	40	16	16
MAINS CABLE No. Cores		3	3	5	5
MAX PIPE LENGTH (m)		75	75	75	75
MAX HEIGHT DIFFERENCE (m)		30	30	30	30
CHARGE R410A (kg) - 30m		5.5	5.5	5.5	5.5

^③ Three Phase



Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland
Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom – Japan – Thailand – Malaysia. ©Mitsubishi Electric Europe 2014. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.



Effective as of May 2014



www.greengateway.mitsubishielectric.co.uk

Mitsubishi Electric UK's commitment to the environment

Follow us @meuk_les
Follow us @green_gateway

in Connect with Green Gateway

YouTube [mitsubishielectric2](https://www.youtube.com/mitsubishielectric2)