## Air Conditioning

### **Product Information**

PLA-SP125BA (Single Phase)
Inverter Heat Pump
4-Way Blow Ceiling Cassette System

Making a World of Difference



Our Inverter range offers customers all the features and benefits of inverter technology whilst being cost effective.

### **Key Features**

- Inverter cassette range only
- Single combination only
- Up to 40m pipe run
- Cost effective with the benefits and features of inverter technology
- Filter lowering operation down to 4m (optional PLP-6BAJ grille required)



Air Conditioning | Heating Ventilation | Controls



# Air Conditioning

### **Product Information**

PLA-SP125BA (Single Phase)
Inverter Heat Pump
4-Way Blow Ceiling Cassette System

Making a World of Difference


PLA-SP - INDOOR UNITS		PLA-SP125BA
CAPACITY (kW)	Heating (nominal)	13.5 (5.0-15.0)
	Cooling (nominal)	12.3 (5.5-13.0)
	Heating (UK)	11.5 (4.3-12.8)
	Cooling (UK)	11.3 (5.1-12.0)
SHF (nominal & UK)		0.71
COP / EER (nominal)		3.41 / 3.01
SCOP / SEER (BS EN14825)		N/A
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	N/A
AIRFLOW (I/s)	Lo-Mi-Mi2-Hi	367-417-467-517
PIPE SIZE mm (in)	Gas/Liquid	15.88 (5/8") / 9.52 (3/8")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Mi2-Hi	34-36-39-41
SOUND POWER LEVEL (dBA)		63
DIMENSIONS (mm)	Width x Depth x Height (Grille)	840 (950) x 840 (950) x 298 (35)
WEIGHT (kg)	Unit / Panel	25 / 6
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6
INTERCONNECTING CABLE No. Cores		4
GRILLE REFERENCE		PLP-6BA
WIRED REMOTE CONTROLLER REFERENCE		PAR-31MAA


PUHZ-SP - OUTDOOR UNITS		PUHZ-SP125VHA
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		55 / 51
SOUND POWER LEVEL (dBA) Cooling		71
WEIGHT (kg)		99
DIMENSIONS (mm)	Width x Depth x Height	950 x 330 + 30 x 1350
ELECTRICAL SUPPLY		220-240v, 50Hz
PHASE		Single
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	4.11 / 4.09
	Heating/Cooling (UK)	3.66 / 3.48
STARTING CURRENT (A)		15.0
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		17.89 / 18.48 [29.0]
FUSE RATING (BS88) - HRC (A)		32
MAINS CABLE No. Cores		3
MAX PIPE LENGTH (m)		40
MAX HEIGHT DIFFERENCE (m)		30
CHARGE R410A (kg)		4.5




### Upper View

**DIMENSIONS** 





#### Front View



 Model
 A
 B
 C
 D
 E

 PLA-SP125BA
 281
 298
 85
 77
 440



Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881
IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland

Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)


Country of origin: United Kingdom – Japan – Thailand – Malaysia. «Missubsish Electric Europe 201.5 Mireguish and Missubsish and Missubsish Electric Europe B.V. The company reserves in right to make any evaluation in technical specification to the equipment described, or to withdraw or replace products in the subsish electric and practice and the equipment described, or to withdraw or replace products in the products and the products. All descriptions liberties is constained before and expensive size of the products. All descriptions, drawings and specifications in this publication present only generate and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sala, a copy of which is available on request. Third-party product and brand ranses may be traditives or registered trademarks of their respective owners.













Mitsubishi Electric UK's commitment to the environment





