



PSA-RP Standard Inverter Heat Pump

Floor Standing System

Our Standard Inverter range offers customers all the features and benefits of inverter technology whilst being cost effective.

The PSA-RP Floor Standing System complements the Mitsubishi Electric range of indoor units. The sleek, modern design of this unit is ideal for numerous applications.

Key Features

- Auto-Restart
- Quiet operation
- Auto-Changeover
- Hot Start - draught prevention
- Factory charged refrigerant up to 30m
- Long-life filter
- Replace Technology available
- Duty Standby Operation
- Demand Control
- Noise Reduction



Air Conditioning

Product Information

PSA-RP Standard Inverter Heat Pump Floor Standing System

Making a
World of
Difference



PSA-RP - INDOOR UNITS		PSA-RP100KA	PSA-RP100KA	PSA-RP125KA	PSA-RP125KA	PSA-RP140KA	PSA-RP140KA
CAPACITY (kW)	Heating (nominal)	11.2 (4.5-12.5)	11.2 (4.5-12.5)	14.0 (5.0-16.0)	14.0 (5.0-16.0)	16.0 (5.0-18.0)	16.0 (5.0-18.0)
	Cooling (nominal)	9.4 (4.9-11.2)	9.4 (4.9-11.2)	12.3 (5.5-14.0)	12.3 (5.5-14.0)	13.6 (5.5-15.0)	13.6 (5.5-15.0)
	Heating (UK)	9.5 (3.85-10.65)	9.5 (3.85-10.65)	11.9 (4.25-13.6)	11.9 (4.25-13.6)	13.6 (4.25-15.3)	13.6 (4.25-15.3)
	Cooling (UK)	8.65 (4.5-10.3)	8.65 (4.5-10.3)	11.3 (5.05-12.9)	11.3 (5.05-12.9)	12.5 (5.06-12.7)	12.5 (5.06-12.7)
SHF (nominal & UK)		0.73	0.73	0.72	0.72	0.71	0.71
COP / EER (nominal)		3.41 / 3.01	3.41 / 3.01	2.81 / 2.81	2.81 / 2.81	2.81 / 2.41	2.81 / 2.41
SCOP / SEER (BS EN14825)		3.8 / 4.6	3.8 / 4.6	3.7 / 3.5	3.7 / 3.5	3.4 / 3.2	3.4 / 3.2
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	A / B	A / B	N/A	N/A	N/A	N/A
AIRFLOW (m³/min)	Lo-Mi-Hi	25-28-30	25-28-30	25-28-31	25-28-31	25-28-31	25-28-31
PIPE SIZE mm (in)	Gas/Liquid	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Hi	45-49-51	45-49-51	45-49-51	45-49-51	45-49-51	45-49-51
SOUND POWER LEVEL (dBA)		65	65	66	66	66	66
DIMENSIONS (mm)	Width x Depth x Height (Grille)	600 x 360 x 1900	600 x 360 x 1900	600 x 360 x 1900	600 x 360 x 1900	600 x 360 x 1900	600 x 360 x 1900
WEIGHT (kg)		46	46	46	46	48	48
ELECTRICAL SUPPLY		Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6	6	6	6	6	6
INTERCONNECTING CABLE No. Cores		4	4	4	4	4	4

PUHZ-P - OUTDOOR UNITS		PUHZ-P100VHA4	PUHZ-P100YHA2 Three Phase	PUHZ-P125VHA3	PUHZ-P125YHA Three Phase	PUHZ-P140VHA3	PUHZ-P140YHA Three Phase
SOUND PRESSURE LEVEL (dBA)	Heating/Cooling	54 / 50	54 / 50	55 / 51	55 / 51	56 / 52	56 / 52
	Cooling	70	70	71	71	73	73
WEIGHT (kg)		75	77	99	101	99	101
DIMENSIONS (mm)	Width x Depth x Height	950 x 330 + 30 x 943	950 x 330 + 30 x 943	950 x 330 + 30 x 1350	950 x 330 + 30 x 1350	950 x 330 + 30 x 1350	950 x 330 + 30 x 1350
ELECTRICAL SUPPLY		220-240v, 50Hz	380-415v, 50Hz	220-240v, 50Hz	380-415v, 50Hz	220-240v, 50Hz	380-415v, 50Hz
PHASE		Single	Three	Single	Three	Single	Three
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	3.280 / 3.120	3.280 / 3.120	4.980 / 4.380	4.980 / 4.380	5.690 / 5.640	5.690 / 5.640
	Heating/Cooling (UK)	2.92 / 2.65	2.92 / 2.65	4.43 / 3.72	4.43 / 3.72	5.06 / 4.79	5.06 / 4.79
STARTING CURRENT (A)		12.0	4.0	15.0	5.0	15.0	5.0
SYSTEM RUNNING CURRENT (A)	Heating/Cooling [MAX]	15.36 / 14.69 [28.7]	5.92 / 5.71 [13.7]	17.47 / 18.10 [28.7]	6.82 / 6.91 [13.7]	22.04 / 23.21 [30.2]	8.31 / 8.65 [13.7]
FUSE RATING (BS88) - HRC (A)		32	16	32	16	40	16
MAINS CABLE No. Cores		3	5	3	5	3	3
MAX PIPE LENGTH (m)		50	50	50	50	50	50
MAX HEIGHT DIFFERENCE (m)		30	30	30	30	30	30
CHARGE R410A (kg)		3.0	3.0	4.5	4.5	4.5	4.5

③ Three Phase



Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881
IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland
Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom - Japan - Thailand - Malaysia. ©Mitsubishi Electric Europe 2014. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.



Effective as of May 2014



www.greengateway.mitsubishielectric.co.uk

Mitsubishi Electric UK's commitment to the environment

Follow us @meuk_les
Follow us @green_gateway

Connect with Green Gateway

mitsubishielectric2