Air Conditioning

Product Information

PSA-RP125KA (Single Phase) **Standard Inverter Heat Pump** Floor Standing System

Making a World of Difference



Our Standard Inverter range offers customers all the features and benefits of inverter technology whilst being cost effective. The PSA-RP Floor Standing System complements the Mitsubishi Electric range of indoor units. The sleek, modern design of this unit is ideal for numerous applications including bars and restaurants.

Key Features

- Built in controller
- Space saving
- Quick and easy installation
- Compact body/minimal space



Air Conditioning | Heating Ventilation | Controls



Product Information

PSA-RP125KA (Single Phase) **Standard Inverter Heat Pump** Floor Standing System

Making a World of Difference

Air Conditioning


PSA-RP - INDOOR UNITS		PSA-RP125KA
CAPACITY (kW)	Heating (nominal)	14.0 (5.0-16.0)
	Cooling (nominal)	12.3 (5.5-14.0)
	Heating (UK)	11.9 (4.25-13.6)
	Cooling (UK)	11.3 (5.05-12.9)
SHF (nominal & UK)		0.72
COP / EER (nominal)		2.81 / 2.81
SCOP / SEER (BS EN14825)		3.7 / 3.5
ErP ENERGY EFFICIENCY CLASS Heating/Cooling		N/A
AIRFLOW (I/s)	Lo-Mi-Hi	417-467-517
PIPE SIZE mm (in)	Gas/Liquid	15.88 (5/8") / 9.52 (3/8")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Hi	45-49-51
SOUND POWER LEVEL (dBA)		66
DIMENSIONS (mm)	Width x Depth x Height (Grille)	600 x 360 x 1900
WEIGHT (kg)	Unit / Panel	46
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6
INTERCONNECTING CABLE No. Cores		4

PUHZ-P - OUTDOOR UNITS	PUHZ-P125VHA3
SOUND PRESSURE LEVEL (dBA) Heating/Cooling	55 / 51
SOUND POWER LEVEL (dBA) Cooling	71
WEIGHT (kg)	99
DIMENSIONS (mm) Width x Depth x Height	950 x 330 + 30 x 1350
ELECTRICAL SUPPLY	220-240v, 50Hz
PHASE	Single
SYSTEM POWER Heating/Cooling (nominal)	4.98 / 4.38
INPUT (kW) Heating/Cooling (UK)	4.43 / 3.72
STARTING CURRENT (A)	15.0
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]	17.47 / 18.10 [28.7]
FUSE RATING (BS88) - HRC (A)	32
MAINS CABLE No. Cores	3
MAX PIPE LENGTH (m)	50
MAX HEIGHT DIFFERENCE (m)	30
CHARGE R410A (kg) - 30m	4.5





DIMENSIONS

Upper View



Front View Side View





Note: When used with a Mr Slim Multi-Split system PSA-RP cannot be connected with indoor units of different types



Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division

Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)


of origin: United Kingdom – Japan – Thalland – Malaysia. @Mitsubishi Electric Europe 2015. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the ake any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing oving its products. All descriptions, illustrations, drawings and specifications in this publication present only igeneral particulars and shall not form part of any contract. All goods are supplied subject to paraly Seneral Conditions of Sale, a copy of which is available on request. Third-party product and brand manner may be trademarks or registered trademarks of their respective owners.













Mitsubishi Electric UK's commitment to the environment





