

Air Conditioning

Product Information

SEZ-KD60VAQ : Inverter Heat Pump

R410A Ceiling Concealed Ducted System



Designed for homes, offices, restaurants or shops, the SEZ series operates at low noise levels and is virtually invisible when installed within a suspended ceiling. Its low unit height and lightweight design also helps to make installation easier and more convenient.

FEATURES



INDOOR


Heating Capacity (kW) (nominal)	7.4 (0.9 - 8)
Cooling Capacity (kW) (nominal)	5.6 (1.1 - 6.3)
Heating Capacity (kW) (UK)	6.2 (0.75 - 6.65)
Cooling Capacity (kW) (UK)	5.55 (1.1 - 6.25)
SHF (nominal and UK)	0.79
COP / EER (nominal)	3.36 / 3.01
SCOP / SEER	3.9 / 5.2
Energy Efficiency Class - Heating / Cooling	A / A
Airflow (m³/min) Lo-Mi-Hi	12 - 15 - 18
Pipe Size Gas (mm [in])	15.88 (5/8")
Pipe Size Liquid (mm [in])	6.35 (1/4")
External Static Pressure (Pa)	5-15-35-50
Sound Pressure Level (dBA) Lo-Mi-Hi	29 - 33 - 37
Sound Power Level (dBA) Cooling	58
Dimensions (mm) Width x Depth x Height	1190 x 700 x 200
Weight (kg)	27
Electrical Supply	FED BY OUTDOOR UNIT
Phase	SINGLE
Fuse Rating (BS88) - HRC (A)	6
Interconnecting Cable No. Cores	4

OUTDOOR

Sound Pressure Level (dBA) Heating / Cooling	55 / 55
Sound Power Level (dBA) Cooling	65
Weight (kg)	50
Dimensions (mm) Width x Depth x Height	840 x 330 x 880
Electrical Supply	220-240V, 50HZ
Phase	SINGLE
System Power Input (kW) - Heating / Cooling (nominal)	2.20 / 1.86
System Power Input (kW) - Heating / Cooling (UK)	1.69 / 1.76
Starting Current (A)	8.57
System Running Current (A) [MAX] - Heating / Cooling	7.93 / 8.09 [14.7]
Fuse Rating (BS88) - HRC (A)	20
Mains Cable No. Cores	3
Max Pipe Length (m)	30
Max Height Difference (m)	30
Charge R410A (kg) - Pre charged length (m)	1.55 - 7

DIMENSIONS

SEZ-KD60VAQ



DIMENSIONS

SUZ-KA60VA3

