
Air Conditioning

Product Information

SLZ-KA Inverter Heat Pump

600 x 600 4-Way Blow Ceiling Cassette System

Making a World of Difference



SLZ-KA Inverter Heat Pump

600 x 600 4-Way Blow Ceiling Cassette System

The SLZ-KA series is perfect for small business applications, as it offers inverter technology alongside quiet operation.

The compact size of this unit is ideal for 600 by 600mm ceilings with a low height, making installation very easy. This unit also comes complete with a long life filter that will last for approximately 2,500 hours.

Key Features

- Swing Vane Mode with Auto Vane Shutter
- Auto-Restart
- Quiet operation
- Auto-Changeover
- Hot Start draught prevention
- Long-life filter
- Drain lift pump as standard
- Low unit height minimal intrusion into occupied space
- Fresh air knockout
- Branch duct knockout
- Ceiling soiling prevention
- Replace Technology available
- Optional interfaces for M-Net connectivity
- DC Fan Motor
- Filter Check Signal



Air Conditioning | Heating Ventilation | Controls



Product Information

Air Conditioning

SLZ-KA Inverter Heat Pump

600 x 600 4-Way Blow Ceiling Cassette System

Making a World of Difference











SLZ-KA-VAQ3 - IND	OOR UNITS	SLZ-KA25VAQ3	SLZ-KA35VAQ3	SLZ-KA50VAQ3
CAPACITY (kW)	Heating (nominal)	3.2 (1.3-4.5)	4.0 (1.7-5.0)	5.0 (1.7-6.5)
, ,	Cooling (nominal)	2.6 (1.5-3.2)	3.5 (1.4-3.9)	4.6 (2.3-5.2)
	Heating (UK)	2.72 (1.11-3.83)	3.4 (1.45-4.25)	4.25 (1.45-5.53)
	Cooling (UK)	2.39 (1.38-2.94)	3.22 (1.29-3.59)	4.23 (2.12-4.78)
SHF (nominal & UK)		0.86	0.77	0.68
COP / EER (nominal)		3.90 / 4.00	3.68 / 3.60	3.25 / 3.30
SCOP / SEER (BS EN14825)	4.3 / 5.5	3.9 / 5.1	4.1 / 5.7
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	A+ / A	A+ / A+	A+ / A+
AIRFLOW (m³/min)	Lo-Mi-Hi	8-9-11	8-9-11	8-9-11
PIPE SIZE mm (in)	Gas	9.52 (3/8")	9.52 (3/8")	12.7 (1/2")
	Liquid	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Hi	29-33-38	29-33-38	30-34-39
SOUND POWER LEVEL (dBA)		57	57	58
DIMENSIONS (mm)	Width x Depth x Height	570 (650) x 570 (650) x 235 (20)	570 (650) x 570 (650) x 235 (20)	570 (650) x 570 (650) x 235 (20)
WEIGHT (kg)	Unit / Grille	16/3	16 / 3	16/3
ELECTRICAL SUPPLY		Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6	6	6
INTERCONNECTING CABLE No. Cores		4	4	4
GRILLE REFERENCE		SLP-2AAW	SLP-2AAW	SLP-2AAW
WIRED REMOTE CONTROLLER REFERENCE		PAR-31MAA	PAR-31MAA	PAR-31MAA

SUZ-KA-VA4 - OUTDOOR UNITS	SUZ-KA25VA4	SUZ-KA35VA4	SUZ-KA50VA4
SOUND PRESSURE LEVEL (dBA) Heating/Cooling	48 / 47	50 / 49	52 / 52
SOUND POWER LEVEL (dBA) Cooling	58	62	65
WEIGHT (kg)	30	35	54
DIMENSIONS (mm) Width x Depth x Height	800 x 285 x 550	800 x 285 x 550	840 x 330 x 880
ELECTRICAL SUPPLY	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
PHASE	Single	Single	Single
SYSTEM POWER Heating/Cooling (nominal)	0.82 / 0.65	1.09 / 0.97	1.55 / 1.39
INPUT (kW) Heating/Cooling (UK)	0.72 / 0.55	0.97 / 0.82	1.38 / 1.18
STARTING CURRENT (A)	4.0	5.1	7.0
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]	3.30 / 4.00 [7.4]	4.80 / 5.10 [8.6]	6.90 / 7.00 [12.4]
FUSE RATING (BS88) - HRC (A)	10	10	20
MAINS CABLE No. Cores	3	3	3
MAX PIPE LENGTH (m)	20	20	30
MAX HEIGHT DIFFERENCE (m)	12	12	30
CHARGE R410A (kg) - 7m	0.8	1.15	1.60



Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland

Country of origin: United Kingdom – Japan – Thalland – Malaysia. @Mitsubish liBectric Europe 2014. Mitsubish and Mitsubish Electric are trademarks of Mitsubish Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public amountement. Mitsubish Electric is constantly developing and improving its products. All descriptions, listilations, dawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on nequest. Third-party product and brand enness may be trademarks or registered trademarks of their respective owners.









Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)





Mitsubishi Electric UK's commitment to the environment



Follow us @meuk_les Follow us @green_gateway



Connect with Green Gateway

