## **Product Information**

## Air Conditioning

SLZ-KF R410A Inverter Heat Pump (Single Phase) 600x600 4-Way Blow Ceiling Cassette System

Making a World of Difference

### Mr.SLIM.



The **SLZ-KF** cassette unit provides the smart solution to comfortable and efficient air conditioning. It combines a stylish square design slimline grille with the latest energy-saving technologies and is designed to fit snugly to ceilings making it ideal in both offices and retail.

#### **Key Features**

- New Design Fits into narrow ceiling spaces with height of only 245mm
- Optional 3D i-see sensor grille provides customised comfort by automatically monitoring room occupancy, position and body temperatures
- Horizontal Airflow eliminating uncomfortable draughts and improving airflow control



Cooling | Heating | Ventilation | Controls

## **Product Information**

# Air Conditioning

**SLZ-KF R410A Inverter Heat Pump (Single Phase)** 600x600 4-Way Blow Ceiling Cassette System

### Making a World of Difference









SLZ-KF-VA2 - I	NDOOR UNITS	SLZ-KF25VA2	SLZ-KF35VA2	SLZ-KF50VA2	SLZ-KF60VA2
CAPACITY (kW)	Heating (nominal)	3.2 (1.3-4.2)	4.0 (1.7-5.0)	5.0 (1.7-6.0)	6.4 (2.5-7.4)
	Cooling (nominal)	2.6 (1.5-3.2)	3.5 (1.4-3.9)	4.6 (2.3-5.2)	5.6 (2.3-6.5)
	Heating (UK)	2.69 (1.09-3.53)	3.36 (1.43-4.20)	4.20 (1.43-5.04)	5.38 (2.10-6.22)
	Cooling (UK)	2.60 (1.50-3.20)	3.46 (1.38-3.86)	4.56 (2.28-5.15)	5.55 (2.28-6.44)
SHF (nominal)		0.78	0.72	0.68	0.68
COP / EER (nominal)		3.61 / 3.8	3.61 / 3.60	3.21 / 3.30	2.81 / 3.17
SCOP / SEER (BS EN14825)		4.3 / 6.3	4.3 / 6.5	4.3/ 6.3	4.1 / 6.2
ErP ENERGY EFFICIENCY CLASS Heating/Cooling		A+ / A++	A+ / A++	A+ / A++	A+ / A++
AIRFLOW (I/s)	Lo-Mi-Hi	108-125-142	108-133-158	117-150-192	125-192-217
PIPE SIZE mm (in)	Gas	9.52 (3/8")	9.52 (3/8")	12.7 (1/2")	15.88 (5/8")
	Liquid	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
SOUND PRESSURE LEVEL (dBA) Lo-Mi-Hi		25-28-31	25-30-33	27-34-39	32-40-43
SOUND POWER LEVEL (dBA)		48	51	56	60
DIMENSIONS (mm)	Width x Depth x Height	570 (650) x 570 (650) x 245 (10)	570 (650) x 570 (650) x 245 (10)	570 (650) x 570 (650) x 245 (10)	570 (650) x 570 (650) x 245 (10)
VEIGHT (kg)	Unit / Grille	15/3	15/3	15 /3	15 /3
ELECTRICAL SUPPLY		Fed by Outdoor Unit			
FUSE RATING (BS88) - HRC (A)		6	6	6	6
INTERCONNECTING CABLE No. Cores		4	4	4	4
GRILLE REFERENCE		SLP-2FA	SLP-2FA	SLP-2FA	SLP-2FA
WIRED REMOTE CONTROLLER REFERENCE		PAR-33MAA	PAR-33MAA	PAR-33MAA	PAR-33MAA

SUZ-KA-VA6 - OUTDOOR UNITS	SUZ-KA25VA6	SUZ-KA35VA6	SUZ-KA50VA6	SUZ-KA60VA6
SOUND PRESSURE LEVEL (dBA) Heating/Cooling	48 / 47	50 / 49	52 / 52	55 / 55
SOUND POWER LEVEL (dBA) Cooling	58	62	65	65
WEIGHT (kg)	30	35	54	50
DIMENSIONS (mm) Width x Depth x Height	800 x 285 x 550	800 x 285 x 550	840 x 330 x 880	840 x 330 x 880
ELECTRICAL SUPPLY	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
PHASE	Single	Single	Single	Single
SYSTEM POWER Heating/Cooling (nominal)	0.89 / 0.68	1.11 / 0.97	1.56 / 1.39	2.28 / 1.77
INPUT (kW) Heating/Cooling (UK)	0.76 / 0.58	0.94 / 0.83	1.33 / 1.20	1.94 / 1.52
STARTING CURRENT (A)	4.2	5.1	7.0	10.1
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]	3.2 / 4.2 (7.2)	4.5 / 5.1 (8.7)	6.3 / 7.0 (12.3)	7.8 / 10.1 (14.4)
FUSE RATING (BS88) - HRC (A)	10	10	20	20
MAINS CABLE No. Cores	3	3	3	3
MAX PIPE LENGTH (m)	20	20	30	30
MAX HEIGHT DIFFERENCE (m)	12	12	30	30
CHARGE REFRIGERANT (kg) / CO <sub>2</sub> EQUIVALENT (t) R410A (GWP 2088) - 7m	0.80 / 1.67	1.15 / 2.40	1.60 / 3.34	1.60 / 3.34
MAX ADDITIONAL REFRIGERANT (kg) / CO2 EQUIVALENT (t) R410A (GWP 2088)	0.39 / 0.81	0.39 / 0.81	0.46 / 0.96	0.46 / 0.96

#### PRODUCT DIMENSIONS

Upper View


82

7.5~24




Side View

SLZ-KF25/35/50/60VA2



Front View



MITSUBISHI ELECTRIC Changes for the Better

408 576~610 Ceiling hol

Telephone: 01707 282880 email: air.conditioning@meuk.mee.com web: airconditioning.mitsubishielectric.co.uk

A (liquid B (gae

UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom – Japan – Thaland – Malaysia. CMItsrubish Electric Europe 2017. Mitsrubish and Mitsrubish Electric are trademarks of Mitsrubish Electric Europe BV. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsrubish Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications to this publication preserves the right to make any variation in Tindy party products. This publication preserves the right to make any variation in Tindy party products and prevent and specifications in this publication preserves the right to make any variation in Tindy party products and brand makes of Materia. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Thirdy party products and brand makes may be trademarks of their respective ownes.

Note: The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electriciar/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Misubiah listicitie's air conditioning equipment and heat pump systems contain a fluorinated greenhouse gas, R4104 (GWP-2088), R42 (GWP-8778), R407C (GWP-1774) or R1344 (GWP-1430). These GWP values are based on Regulation (EU) to 8172/2014 from IPCC 4th addition. Tics Soft Regulation (EU) No.628/2014 from IPCC 3th addition. Mesh are as follows. R4104 (GWP-1578), R42 (GWP-8778), R4470 (GWP-8784), R448 (GWP-1300).





Living Environmental System

thehub.mitsubishielectric.co.uk